

性能参数列表 Performance Matrix Table

XR22B-C1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				1.67	2.04	2.47	2.98	3.58	4.29
	60			1.48	1.81	2.20	2.66	3.20	3.82	4.57
	55	1.02	1.29	1.59	1.95	2.36	2.84	3.40	4.06	4.83
	50	1.10	1.37	1.70	2.07	2.51	3.01	3.60	4.28	5.09
	45	1.16	1.46	1.80	2.19	2.65	3.18	3.79	4.50	5.34
	40	1.23	1.53	1.89	2.30	2.78	3.34	3.98	4.72	5.60
	35	1.28	1.60	1.98	2.41	2.91	3.49	4.16	4.95	5.86
	30	1.33	1.67	2.06	2.52	3.04	3.65	4.36	5.17	6.13
	25	1.38	1.73	2.14	2.62	3.17	3.81	4.55	5.41	
	20	1.42	1.79	2.22	2.72	3.30	3.98	4.76		
	15	1.47	1.85	2.30	2.83	3.44	4.15			
10	1.50	1.91	2.38	2.94	3.59					
Input Power	65				2.22	2.32	2.40	2.48	2.56	2.62
	60			1.92	2.01	2.09	2.18	2.25	2.32	2.39
	55	1.57	1.66	1.74	1.83	1.91	1.98	2.05	2.12	2.18
	50	1.43	1.51	1.59	1.67	1.74	1.81	1.88	1.95	2.01
	45	1.32	1.39	1.46	1.53	1.60	1.67	1.73	1.80	1.85
	40	1.21	1.28	1.34	1.41	1.47	1.54	1.60	1.66	1.72
	35	1.11	1.17	1.23	1.29	1.36	1.42	1.48	1.53	1.59
	30	1.02	1.07	1.13	1.18	1.24	1.30	1.36	1.41	1.47
	25	0.92	0.97	1.02	1.07	1.13	1.18	1.24	1.29	
	20	0.82	0.86	0.91	0.95	1.00	1.06	1.11		
	15	0.70	0.74	0.78	0.82	0.87	0.92			
10	0.56	0.59	0.63	0.67	0.72					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR28B-C1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				1.94	2.37	2.87	3.46	4.15	4.98
	60			1.71	2.10	2.56	3.09	3.70	4.43	5.29
	55	1.19	1.49	1.84	2.26	2.74	3.29	3.94	4.70	5.60
	50	1.27	1.59	1.97	2.40	2.91	3.49	4.17	4.96	5.90
	45	1.35	1.69	2.08	2.54	3.07	3.68	4.39	5.22	6.19
	40	1.42	1.78	2.19	2.67	3.23	3.87	4.61	5.48	6.49
	35	1.49	1.86	2.29	2.80	3.38	4.05	4.83	5.73	6.79
	30	1.55	1.94	2.39	2.92	3.53	4.23	5.05	6.00	7.11
	25	1.60	2.01	2.48	3.04	3.68	4.42	5.28	6.28	
	20	1.65	2.08	2.58	3.16	3.83	4.61	5.52		
	15	1.70	2.14	2.67	3.28	3.99	4.82			
10	1.74	2.21	2.76	3.41	4.16					
Input Power	65				2.35	2.44	2.54	2.62	2.70	2.77
	60			2.03	2.12	2.21	2.30	2.38	2.45	2.52
	55	1.66	1.75	1.84	1.93	2.01	2.09	2.17	2.24	2.31
	50	1.51	1.60	1.68	1.76	1.84	1.92	1.99	2.06	2.12
	45	1.39	1.47	1.54	1.62	1.69	1.76	1.83	1.90	1.96
	40	1.28	1.35	1.42	1.49	1.56	1.62	1.69	1.75	1.81
	35	1.18	1.24	1.30	1.37	1.43	1.50	1.56	1.62	1.68
	30	1.08	1.13	1.19	1.25	1.31	1.37	1.43	1.49	1.55
	25	0.97	1.02	1.08	1.13	1.19	1.25	1.31	1.36	
	20	0.86	0.91	0.96	1.01	1.06	1.12	1.17		
	15	0.74	0.78	0.82	0.87	0.92	0.97			
10	0.59	0.63	0.67	0.71	0.76					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表 Performance Matrix Table

XR32B-C1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				2.37	2.89	3.51	4.23	5.08	6.09
	60			2.10	2.57	3.13	3.77	4.53	5.42	6.48
	55	1.45	1.82	2.26	2.76	3.35	4.03	4.82	5.75	6.85
	50	1.56	1.95	2.41	2.94	3.56	4.27	5.10	6.07	7.21
	45	1.65	2.06	2.55	3.11	3.75	4.50	5.37	6.39	7.57
	40	1.74	2.17	2.68	3.27	3.95	4.73	5.64	6.70	7.94
	35	1.82	2.27	2.81	3.42	4.13	4.95	5.91	7.01	8.31
	30	1.89	2.37	2.92	3.57	4.32	5.18	6.18	7.34	8.70
	25	1.96	2.46	3.04	3.72	4.50	5.41	6.46	7.68	
	20	2.02	2.54	3.15	3.86	4.69	5.64	6.75		
	15	2.08	2.62	3.26	4.01	4.88	5.89			
10	2.13	2.70	3.38	4.17	5.08					
Input Power	65				2.71	2.82	2.92	3.02	3.11	3.19
	60			2.34	2.45	2.55	2.65	2.74	2.83	2.91
	55	1.92	2.02	2.12	2.22	2.32	2.41	2.50	2.58	2.66
	50	1.75	1.84	1.94	2.03	2.12	2.21	2.29	2.37	2.45
	45	1.60	1.69	1.78	1.86	1.95	2.03	2.11	2.19	2.26
	40	1.47	1.55	1.63	1.71	1.79	1.87	1.95	2.02	2.09
	35	1.36	1.43	1.50	1.58	1.65	1.73	1.80	1.87	1.94
	30	1.24	1.31	1.37	1.44	1.51	1.58	1.65	1.72	1.79
	25	1.12	1.18	1.24	1.31	1.37	1.44	1.51	1.57	
	20	1.00	1.05	1.10	1.16	1.22	1.29	1.35		
	15	0.85	0.90	0.95	1.00	1.06	1.12			
10	0.68	0.72	0.77	0.82	0.88					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR38B-C1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				2.72	3.31	4.02	4.84	5.81	6.97
	60			2.40	2.95	3.58	4.32	5.19	6.21	7.42
	55	1.66	2.09	2.58	3.16	3.83	4.61	5.52	6.59	7.85
	50	1.78	2.23	2.76	3.37	4.07	4.89	5.84	6.96	8.26
	45	1.89	2.36	2.92	3.56	4.30	5.16	6.15	7.31	8.68
	40	1.99	2.49	3.07	3.74	4.52	5.42	6.46	7.67	9.09
	35	2.08	2.60	3.21	3.92	4.73	5.68	6.77	8.03	9.52
	30	2.17	2.71	3.35	4.09	4.94	5.93	7.08	8.41	9.96
	25	2.24	2.81	3.48	4.26	5.15	6.19	7.40	8.80	
	20	2.31	2.91	3.61	4.42	5.37	6.46	7.73		
	15	2.38	3.00	3.74	4.59	5.59	6.75			
10	2.44	3.10	3.87	4.77	5.82					
Input Power	65				2.94	3.06	3.17	3.27	3.37	3.46
	60			2.53	2.65	2.76	2.87	2.97	3.06	3.15
	55	2.08	2.19	2.30	2.41	2.52	2.62	2.71	2.80	2.88
	50	1.89	2.00	2.10	2.20	2.30	2.40	2.49	2.57	2.65
	45	1.74	1.83	1.93	2.02	2.11	2.20	2.29	2.37	2.45
	40	1.60	1.68	1.77	1.86	1.94	2.03	2.11	2.19	2.27
	35	1.47	1.55	1.63	1.71	1.79	1.87	1.95	2.02	2.10
	30	1.35	1.42	1.49	1.56	1.64	1.72	1.79	1.87	1.94
	25	1.22	1.28	1.35	1.42	1.49	1.56	1.63	1.71	
	20	1.08	1.13	1.19	1.26	1.33	1.40	1.47		
	15	0.92	0.97	1.03	1.09	1.15	1.22			
10	0.74	0.78	0.83	0.89	0.95					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR45B-C1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				3.20	3.91	4.74	5.71	6.86	8.22
	60			2.83	3.47	4.22	5.10	6.12	7.32	8.75
	55	1.96	2.46	3.05	3.73	4.52	5.44	6.51	7.77	9.25
	50	2.10	2.63	3.25	3.97	4.80	5.77	6.89	8.20	9.74
	45	2.23	2.79	3.44	4.20	5.07	6.08	7.26	8.62	10.23
	40	2.35	2.93	3.62	4.41	5.33	6.39	7.62	9.04	10.72
	35	2.45	3.07	3.79	4.62	5.58	6.69	7.98	9.47	11.22
	30	2.55	3.20	3.95	4.82	5.83	6.99	8.34	9.91	11.74
	25	2.64	3.32	4.10	5.02	6.08	7.30	8.72	10.37	
	20	2.73	3.43	4.26	5.22	6.33	7.62	9.12		
	15	2.81	3.54	4.41	5.42	6.59	7.95			
10	2.88	3.65	4.56	5.62	6.87					
Input Power	65				3.43	3.57	3.70	3.82	3.94	4.04
	60			2.96	3.10	3.23	3.35	3.47	3.58	3.68
	55	2.42	2.56	2.69	2.81	2.94	3.05	3.17	3.27	3.37
	50	2.21	2.33	2.45	2.57	2.69	2.80	2.90	3.00	3.09
	45	2.03	2.14	2.25	2.36	2.47	2.57	2.67	2.77	2.86
	40	1.87	1.97	2.07	2.17	2.27	2.37	2.47	2.56	2.65
	35	1.72	1.81	1.90	1.99	2.09	2.18	2.27	2.36	2.45
	30	1.57	1.65	1.74	1.82	1.91	2.00	2.09	2.18	2.26
	25	1.42	1.49	1.57	1.65	1.74	1.82	1.91	1.99	
	20	1.26	1.32	1.39	1.47	1.55	1.63	1.71		
	15	1.08	1.13	1.20	1.27	1.34	1.42			
10	0.87	0.91	0.97	1.04	1.11					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR52B-C1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				3.72	4.54	5.51	6.64	7.97	9.56
	60			3.29	4.04	4.91	5.93	7.12	8.51	10.17
	55	2.28	2.86	3.54	4.33	5.26	6.33	7.57	9.03	10.76
	50	2.44	3.06	3.78	4.61	5.58	6.71	8.01	9.54	11.33
	45	2.59	3.24	4.00	4.88	5.90	7.07	8.44	10.03	11.89
	40	2.73	3.41	4.21	5.13	6.20	7.43	8.86	10.52	12.46
	35	2.85	3.57	4.41	5.37	6.49	7.78	9.28	11.01	13.05
	30	2.97	3.72	4.59	5.61	6.78	8.13	9.70	11.52	13.66
	25	3.07	3.86	4.77	5.84	7.07	8.49	10.14	12.06	
	20	3.17	3.99	4.95	6.07	7.36	8.86	10.60		
	15	3.26	4.12	5.12	6.30	7.66	9.25			
10	3.35	4.25	5.30	6.54	7.99					
Input Power	65				3.92	4.08	4.23	4.37	4.50	4.62
	60			3.39	3.54	3.69	3.83	3.97	4.09	4.21
	55	2.77	2.92	3.07	3.22	3.36	3.49	3.62	3.74	3.85
	50	2.53	2.67	2.80	2.94	3.07	3.20	3.32	3.43	3.54
	45	2.32	2.45	2.57	2.70	2.82	2.94	3.06	3.16	3.27
	40	2.13	2.25	2.36	2.48	2.60	2.71	2.82	2.92	3.02
	35	1.96	2.07	2.17	2.28	2.39	2.50	2.60	2.70	2.80
	30	1.80	1.89	1.99	2.09	2.19	2.29	2.39	2.49	2.59
	25	1.63	1.71	1.80	1.89	1.99	2.08	2.18	2.28	
	20	1.44	1.51	1.59	1.68	1.77	1.86	1.96		
	15	1.23	1.30	1.37	1.45	1.53	1.62			
10	0.99	1.05	1.11	1.19	1.27					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR63B-C1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				4.50	5.50	6.66	8.03	9.64	11.56
	60			3.98	4.88	5.94	7.17	8.61	10.30	12.30
	55	2.76	3.46	4.28	5.24	6.35	7.65	9.16	10.92	13.01
	50	2.95	3.70	4.57	5.58	6.75	8.11	9.69	11.53	13.70
	45	3.13	3.92	4.84	5.90	7.13	8.55	10.20	12.13	14.38
	40	3.30	4.13	5.09	6.20	7.49	8.98	10.71	12.72	15.07
	35	3.45	4.32	5.33	6.50	7.85	9.41	11.22	13.32	15.78
	30	3.59	4.50	5.55	6.78	8.20	9.83	11.73	13.94	16.52
	25	3.72	4.67	5.77	7.06	8.54	10.27	12.26	14.58	
	20	3.84	4.83	5.98	7.33	8.90	10.71	12.82		
	15	3.95	4.98	6.20	7.62	9.27	11.19			
10	4.05	5.13	6.41	7.91	9.66					
Input Power	65				5.13	5.34	5.54	5.72	5.89	6.05
	60			4.43	4.63	4.83	5.02	5.19	5.36	5.51
	55	3.63	3.83	4.02	4.21	4.40	4.57	4.74	4.89	5.04
	50	3.31	3.49	3.67	3.85	4.02	4.19	4.34	4.49	4.63
	45	3.03	3.20	3.37	3.53	3.69	3.85	4.00	4.14	4.28
	40	2.79	2.94	3.09	3.25	3.40	3.55	3.69	3.83	3.96
	35	2.57	2.70	2.84	2.98	3.13	3.27	3.40	3.54	3.67
	30	2.35	2.47	2.60	2.73	2.86	3.00	3.13	3.26	3.39
	25	2.13	2.24	2.35	2.47	2.60	2.73	2.85	2.98	
	20	1.89	1.98	2.09	2.20	2.32	2.44	2.56		
	15	1.61	1.70	1.79	1.90	2.01	2.13			
10	1.29	1.37	1.46	1.55	1.66					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR72B-C1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				5.25	6.41	7.77	9.36	11.25	13.49
	60			4.64	5.70	6.93	8.36	10.04	12.01	14.35
	55	3.22	4.04	5.00	6.12	7.41	8.92	10.68	12.74	15.18
	50	3.45	4.32	5.33	6.51	7.88	9.46	11.30	13.45	15.98
	45	3.66	4.57	5.64	6.88	8.32	9.98	11.90	14.15	16.78
	40	3.85	4.81	5.94	7.24	8.74	10.48	12.49	14.84	17.58
	35	4.03	5.04	6.21	7.58	9.16	10.98	13.09	15.54	18.41
	30	4.19	5.25	6.48	7.91	9.56	11.47	13.68	16.26	19.27
	25	4.34	5.44	6.73	8.23	9.97	11.98	14.30	17.01	
	20	4.48	5.63	6.98	8.56	10.38	12.50	14.96		
	15	4.60	5.81	7.23	8.89	10.81	13.05			
10	4.73	5.99	7.48	9.23	11.27					
Input Power	65				5.85	6.09	6.32	6.53	6.72	6.90
	60			5.05	5.29	5.51	5.72	5.92	6.11	6.28
	55	4.14	4.36	4.59	4.80	5.01	5.21	5.40	5.58	5.74
	50	3.77	3.98	4.19	4.39	4.58	4.77	4.95	5.12	5.28
	45	3.46	3.65	3.84	4.03	4.21	4.39	4.56	4.72	4.88
	40	3.18	3.36	3.53	3.70	3.88	4.04	4.21	4.37	4.52
	35	2.93	3.08	3.24	3.40	3.57	3.73	3.88	4.04	4.18
	30	2.68	2.82	2.97	3.11	3.27	3.42	3.57	3.72	3.86
	25	2.43	2.55	2.68	2.82	2.96	3.11	3.26	3.40	
	20	2.15	2.26	2.38	2.51	2.64	2.78	2.92		
	15	1.84	1.94	2.04	2.16	2.29	2.42			
10	1.48	1.56	1.66	1.77	1.89					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表 Performance Matrix Table

XR91B-C1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	60			5.46	6.70	8.15	9.84	11.81	14.13	
	55	3.79	4.75	5.88	7.19	8.72	10.50	12.57	14.99	17.85
	50	4.05	5.08	6.27	7.66	9.27	11.13	13.30	15.82	18.80
	45	4.30	5.38	6.64	8.10	9.79	11.74	14.00	16.64	19.74
	40	4.53	5.66	6.98	8.52	10.28	12.33	14.70	17.45	20.68
	35	4.74	5.93	7.31	8.92	10.77	12.91	15.39	18.28	21.65
	30	4.93	6.17	7.62	9.30	11.25	13.50	16.10	19.12	22.67
	25	5.10	6.40	7.92	9.68	11.73	14.09	16.83	20.01	
	20	5.26	6.62	8.21	10.07	12.21	14.70	17.59		
	15	5.42	6.84	8.50	10.45	12.72	15.35			
10	5.56	7.05	8.80	10.85	13.25					
Input Power	60			5.90	6.17	6.43	6.68	6.91	7.13	
	55	4.83	5.09	5.35	5.61	5.85	6.08	6.31	6.51	6.70
	50	4.40	4.65	4.89	5.12	5.35	5.57	5.78	5.98	6.16
	45	4.04	4.26	4.48	4.70	4.91	5.12	5.32	5.51	5.69
	40	3.72	3.92	4.12	4.32	4.52	4.72	4.91	5.09	5.27
	35	3.42	3.60	3.78	3.97	4.16	4.35	4.53	4.71	4.88
	30	3.13	3.29	3.46	3.63	3.81	3.99	4.17	4.34	4.51
	25	2.83	2.98	3.13	3.29	3.46	3.63	3.80	3.97	
	20	2.51	2.64	2.78	2.93	3.08	3.25	3.41		
	15	2.15	2.26	2.39	2.52	2.67	2.83			
10	1.72	1.82	1.94	2.07	2.21					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR22B-D1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				1.69	2.06	2.49	3.01	3.61	4.33
	60			1.49	1.83	2.22	2.68	3.22	3.86	4.61
	55	1.03	1.30	1.60	1.96	2.38	2.86	3.43	4.09	4.87
	50	1.11	1.39	1.71	2.09	2.53	3.04	3.63	4.32	5.13
	45	1.17	1.47	1.81	2.21	2.67	3.20	3.82	4.54	5.39
	40	1.24	1.55	1.91	2.32	2.81	3.36	4.01	4.76	5.64
	35	1.29	1.62	2.00	2.43	2.94	3.52	4.20	4.99	5.91
	30	1.34	1.68	2.08	2.54	3.07	3.68	4.39	5.22	6.19
	25	1.39	1.75	2.16	2.64	3.20	3.84	4.59	5.46	
	20	1.44	1.81	2.24	2.75	3.33	4.01	4.80		
	15	1.48	1.87	2.32	2.85	3.47	4.19			
10	1.52	1.92	2.40	2.96	3.62					
Input Power	65				1.99	2.07	2.14	2.22	2.28	2.34
	60			1.72	1.79	1.87	1.94	2.01	2.07	2.13
	55	1.40	1.48	1.56	1.63	1.70	1.77	1.83	1.89	1.95
	50	1.28	1.35	1.42	1.49	1.56	1.62	1.68	1.74	1.79
	45	1.17	1.24	1.30	1.37	1.43	1.49	1.55	1.60	1.66
	40	1.08	1.14	1.20	1.26	1.32	1.37	1.43	1.48	1.53
	35	0.99	1.05	1.10	1.16	1.21	1.26	1.32	1.37	1.42
	30	0.91	0.96	1.01	1.06	1.11	1.16	1.21	1.26	1.31
	25	0.82	0.87	0.91	0.96	1.01	1.06	1.11	1.15	
	20	0.73	0.77	0.81	0.85	0.90	0.94	0.99		
	15	0.62	0.66	0.69	0.73	0.78	0.82			
10	0.50	0.53	0.56	0.60	0.64					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR28B-D1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				1.96	2.40	2.90	3.50	4.20	5.04
	60			1.73	2.13	2.59	3.12	3.75	4.49	5.36
	55	1.20	1.51	1.87	2.29	2.77	3.33	3.99	4.76	5.67
	50	1.29	1.61	1.99	2.43	2.94	3.54	4.22	5.03	5.97
	45	1.37	1.71	2.11	2.57	3.11	3.73	4.45	5.29	6.27
	40	1.44	1.80	2.22	2.71	3.27	3.92	4.67	5.54	6.57
	35	1.51	1.88	2.32	2.83	3.42	4.10	4.89	5.81	6.88
	30	1.57	1.96	2.42	2.96	3.57	4.29	5.11	6.08	7.20
	25	1.62	2.03	2.52	3.08	3.73	4.48	5.35	6.36	
	20	1.67	2.10	2.61	3.20	3.88	4.67	5.59		
	15	1.72	2.17	2.70	3.32	4.04	4.88			
10	1.77	2.24	2.80	3.45	4.21					
Input Power	65				2.18	2.27	2.35	2.43	2.50	2.57
	60			1.88	1.97	2.05	2.13	2.21	2.28	2.34
	55	1.54	1.62	1.71	1.79	1.87	1.94	2.01	2.08	2.14
	50	1.41	1.48	1.56	1.63	1.71	1.78	1.85	1.91	1.97
	45	1.29	1.36	1.43	1.50	1.57	1.63	1.70	1.76	1.82
	40	1.19	1.25	1.31	1.38	1.44	1.51	1.57	1.63	1.68
	35	1.09	1.15	1.21	1.27	1.33	1.39	1.45	1.50	1.56
	30	1.00	1.05	1.10	1.16	1.22	1.27	1.33	1.38	1.44
	25	0.90	0.95	1.00	1.05	1.10	1.16	1.21	1.27	
	20	0.80	0.84	0.89	0.93	0.98	1.04	1.09		
	15	0.68	0.72	0.76	0.81	0.85	0.90			
10	0.55	0.58	0.62	0.66	0.70					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR32B-D1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				2.39	2.91	3.53	4.25	5.11	6.12
	60			2.11	2.59	3.15	3.80	4.56	5.45	6.52
	55	1.46	1.83	2.27	2.78	3.37	4.05	4.85	5.79	6.89
	50	1.57	1.96	2.42	2.96	3.58	4.30	5.13	6.11	7.26
	45	1.66	2.08	2.56	3.13	3.78	4.53	5.41	6.42	7.62
	40	1.75	2.19	2.70	3.29	3.97	4.76	5.67	6.74	7.98
	35	1.83	2.29	2.82	3.44	4.16	4.98	5.94	7.06	8.36
	30	1.90	2.38	2.94	3.59	4.34	5.21	6.21	7.38	8.75
	25	1.97	2.47	3.06	3.74	4.53	5.44	6.50	7.73	
	20	2.03	2.56	3.17	3.89	4.71	5.68	6.79		
	15	2.09	2.64	3.28	4.04	4.91	5.93			
10	2.15	2.72	3.40	4.19	5.12					
Input Power	65				2.58	2.68	2.78	2.88	2.96	3.04
	60			2.23	2.33	2.43	2.52	2.61	2.69	2.77
	55	1.82	1.92	2.02	2.12	2.21	2.30	2.38	2.46	2.53
	50	1.66	1.75	1.84	1.93	2.02	2.10	2.18	2.26	2.33
	45	1.52	1.61	1.69	1.77	1.85	1.93	2.01	2.08	2.15
	40	1.40	1.48	1.55	1.63	1.71	1.78	1.85	1.92	1.99
	35	1.29	1.36	1.43	1.50	1.57	1.64	1.71	1.78	1.84
	30	1.18	1.24	1.31	1.37	1.44	1.51	1.57	1.64	1.70
	25	1.07	1.12	1.18	1.24	1.31	1.37	1.43	1.50	
	20	0.95	1.00	1.05	1.11	1.16	1.23	1.29		
	15	0.81	0.85	0.90	0.95	1.01	1.07			
10	0.65	0.69	0.73	0.78	0.83					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR38B-D1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				2.72	3.31	4.02	4.84	5.81	6.97
	60			2.40	2.95	3.58	4.32	5.19	6.21	7.42
	55	1.66	2.09	2.58	3.16	3.83	4.61	5.52	6.59	7.85
	50	1.78	2.23	2.76	3.37	4.07	4.89	5.84	6.96	8.26
	45	1.89	2.36	2.92	3.56	4.30	5.16	6.15	7.31	8.68
	40	1.99	2.49	3.07	3.74	4.52	5.42	6.46	7.67	9.09
	35	2.08	2.60	3.21	3.92	4.73	5.68	6.77	8.03	9.52
	30	2.17	2.71	3.35	4.09	4.94	5.93	7.08	8.41	9.96
	25	2.24	2.81	3.48	4.26	5.15	6.19	7.40	8.80	
	20	2.31	2.91	3.61	4.42	5.37	6.46	7.73		
	15	2.38	3.00	3.74	4.59	5.59	6.75			
10	2.44	3.10	3.87	4.77	5.82					
Input Power	65				2.89	3.01	3.12	3.22	3.32	3.41
	60			2.50	2.61	2.72	2.83	2.93	3.02	3.10
	55	2.04	2.16	2.27	2.37	2.48	2.58	2.67	2.76	2.84
	50	1.86	1.97	2.07	2.17	2.26	2.36	2.45	2.53	2.61
	45	1.71	1.80	1.90	1.99	2.08	2.17	2.25	2.33	2.41
	40	1.57	1.66	1.74	1.83	1.91	2.00	2.08	2.16	2.23
	35	1.45	1.52	1.60	1.68	1.76	1.84	1.92	1.99	2.07
	30	1.32	1.39	1.46	1.54	1.61	1.69	1.76	1.84	1.91
	25	1.20	1.26	1.33	1.39	1.46	1.54	1.61	1.68	
	20	1.06	1.12	1.18	1.24	1.31	1.37	1.44		
	15	0.91	0.96	1.01	1.07	1.13	1.20			
10	0.73	0.77	0.82	0.87	0.93					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR45B-D1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				3.21	3.92	4.75	5.72	6.87	8.24
	60			2.84	3.48	4.23	5.11	6.13	7.34	8.76
	55	1.97	2.47	3.05	3.74	4.53	5.45	6.53	7.79	9.27
	50	2.11	2.64	3.26	3.98	4.81	5.78	6.90	8.22	9.76
	45	2.23	2.79	3.45	4.21	5.08	6.10	7.27	8.64	10.25
	40	2.35	2.94	3.63	4.42	5.34	6.40	7.63	9.06	10.74
	35	2.46	3.08	3.80	4.63	5.59	6.71	7.99	9.49	11.24
	30	2.56	3.20	3.96	4.83	5.84	7.01	8.36	9.93	11.77
	25	2.65	3.32	4.11	5.03	6.09	7.32	8.74	10.39	
	20	2.73	3.44	4.27	5.23	6.34	7.64	9.14		
	15	2.81	3.55	4.42	5.43	6.61	7.97			
10	2.89	3.66	4.57	5.64	6.88					
Input Power	65				3.38	3.52	3.65	3.77	3.89	3.99
	60			2.92	3.06	3.19	3.31	3.43	3.53	3.63
	55	2.39	2.52	2.65	2.78	2.90	3.02	3.13	3.23	3.32
	50	2.18	2.30	2.42	2.54	2.65	2.76	2.87	2.96	3.05
	45	2.00	2.11	2.22	2.33	2.43	2.54	2.64	2.73	2.82
	40	1.84	1.94	2.04	2.14	2.24	2.34	2.43	2.53	2.61
	35	1.69	1.78	1.88	1.97	2.06	2.15	2.25	2.33	2.42
	30	1.55	1.63	1.72	1.80	1.89	1.98	2.06	2.15	2.23
	25	1.40	1.48	1.55	1.63	1.71	1.80	1.88	1.97	
	20	1.24	1.31	1.38	1.45	1.53	1.61	1.69		
	15	1.06	1.12	1.18	1.25	1.32	1.40			
10	0.85	0.90	0.96	1.02	1.09					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR52B-D1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				3.73	4.55	5.52	6.65	7.99	9.58
	60			3.30	4.05	4.92	5.94	7.13	8.53	10.19
	55	2.29	2.87	3.55	4.34	5.27	6.34	7.59	9.05	10.78
	50	2.45	3.06	3.79	4.62	5.59	6.72	8.03	9.55	11.35
	45	2.60	3.25	4.01	4.89	5.91	7.09	8.45	10.05	11.92
	40	2.73	3.42	4.22	5.14	6.21	7.44	8.87	10.54	12.49
	35	2.86	3.58	4.41	5.38	6.50	7.80	9.29	11.03	13.07
	30	2.98	3.73	4.60	5.62	6.79	8.15	9.72	11.55	13.68
	25	3.08	3.87	4.78	5.85	7.08	8.51	10.16	12.08	
	20	3.18	4.00	4.96	6.08	7.37	8.88	10.62		
	15	3.27	4.13	5.13	6.31	7.68	9.27			
10	3.36	4.25	5.31	6.55	8.00					
Input Power	65				3.87	4.03	4.18	4.32	4.45	4.57
	60			3.35	3.50	3.65	3.79	3.92	4.05	4.16
	55	2.74	2.89	3.04	3.18	3.32	3.45	3.58	3.70	3.80
	50	2.50	2.64	2.77	2.91	3.04	3.16	3.28	3.39	3.50
	45	2.29	2.42	2.54	2.67	2.79	2.91	3.02	3.13	3.23
	40	2.11	2.22	2.34	2.45	2.57	2.68	2.79	2.89	2.99
	35	1.94	2.04	2.15	2.25	2.36	2.47	2.57	2.67	2.77
	30	1.78	1.87	1.96	2.06	2.16	2.26	2.36	2.46	2.56
	25	1.61	1.69	1.78	1.87	1.96	2.06	2.16	2.25	
	20	1.42	1.50	1.58	1.66	1.75	1.84	1.94		
	15	1.22	1.28	1.35	1.43	1.52	1.61			
10	0.98	1.03	1.10	1.17	1.25					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR63B-D1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				4.52	5.51	6.68	8.05	9.67	11.60
	60			3.99	4.90	5.96	7.19	8.63	10.33	12.34
	55	2.77	3.47	4.30	5.26	6.38	7.67	9.19	10.96	13.05
	50	2.96	3.71	4.58	5.60	6.77	8.14	9.72	11.57	13.74
	45	3.14	3.93	4.85	5.92	7.15	8.58	10.24	12.16	14.43
	40	3.31	4.14	5.11	6.22	7.52	9.01	10.74	12.76	15.12
	35	3.46	4.33	5.34	6.52	7.87	9.44	11.25	13.36	15.83
	30	3.60	4.51	5.57	6.80	8.22	9.87	11.77	13.98	16.57
	25	3.73	4.68	5.79	7.08	8.57	10.30	12.30	14.63	
	20	3.85	4.84	6.00	7.36	8.93	10.75	12.86		
	15	3.96	5.00	6.22	7.64	9.30	11.22			
10	4.06	5.15	6.43	7.93	9.69					
Input Power	65				4.60	4.79	4.97	5.13	5.29	5.43
	60			3.97	4.16	4.33	4.50	4.66	4.81	4.94
	55	3.25	3.43	3.61	3.78	3.94	4.10	4.25	4.39	4.52
	50	2.97	3.13	3.29	3.45	3.61	3.76	3.90	4.03	4.15
	45	2.72	2.87	3.02	3.17	3.31	3.45	3.59	3.72	3.84
	40	2.50	2.64	2.78	2.91	3.05	3.18	3.31	3.43	3.55
	35	2.30	2.43	2.55	2.68	2.80	2.93	3.05	3.17	3.29
	30	2.11	2.22	2.33	2.45	2.57	2.69	2.81	2.92	3.04
	25	1.91	2.01	2.11	2.22	2.33	2.45	2.56	2.67	
	20	1.69	1.78	1.87	1.97	2.08	2.19	2.30		
	15	1.45	1.52	1.61	1.70	1.80	1.91			
10	1.16	1.23	1.31	1.39	1.49					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR72B-D1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				5.15	6.29	7.62	9.18	11.03	13.22
	60			4.55	5.58	6.79	8.20	9.84	11.78	14.06
	55	3.15	3.96	4.90	5.99	7.27	8.75	10.47	12.49	14.88
	50	3.38	4.23	5.23	6.38	7.72	9.27	11.08	13.19	15.67
	45	3.59	4.48	5.53	6.75	8.15	9.78	11.67	13.87	16.45
	40	3.77	4.72	5.82	7.10	8.57	10.27	12.25	14.55	17.24
	35	3.95	4.94	6.09	7.43	8.98	10.76	12.83	15.23	18.04
	30	4.11	5.14	6.35	7.75	9.37	11.25	13.42	15.94	18.89
	25	4.25	5.34	6.60	8.07	9.77	11.74	14.02	16.68	
	20	4.39	5.52	6.84	8.39	10.18	12.25	14.66		
	15	4.51	5.70	7.09	8.71	10.60	12.79			
10	4.63	5.87	7.33	9.05	11.04					
Input Power	65				5.15	5.36	5.56	5.75	5.92	6.08
	60			4.45	4.66	4.85	5.04	5.22	5.38	5.53
	55	3.64	3.84	4.04	4.23	4.42	4.59	4.76	4.92	5.06
	50	3.32	3.51	3.69	3.87	4.04	4.21	4.36	4.51	4.65
	45	3.05	3.21	3.38	3.55	3.71	3.87	4.02	4.16	4.30
	40	2.80	2.96	3.11	3.26	3.41	3.56	3.71	3.85	3.98
	35	2.58	2.72	2.86	3.00	3.14	3.28	3.42	3.55	3.68
	30	2.36	2.48	2.61	2.74	2.88	3.01	3.14	3.28	3.40
	25	2.14	2.25	2.36	2.48	2.61	2.74	2.87	3.00	
	20	1.89	1.99	2.10	2.21	2.33	2.45	2.58		
	15	1.62	1.70	1.80	1.91	2.02	2.13			
10	1.30	1.38	1.46	1.56	1.67					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR91B-D1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				6.47	7.89	9.57	11.53	13.85	16.61
	60			5.72	7.01	8.53	10.30	12.36	14.79	17.67
	55	3.96	4.97	6.15	7.53	9.13	10.99	13.15	15.69	18.69
	50	4.24	5.31	6.56	8.02	9.70	11.65	13.92	16.56	19.68
	45	4.50	5.63	6.95	8.48	10.24	12.29	14.66	17.42	20.66
	40	4.74	5.93	7.31	8.91	10.77	12.91	15.38	18.27	21.65
	35	4.96	6.20	7.65	9.33	11.27	13.52	16.11	19.13	22.67
	30	5.16	6.46	7.98	9.74	11.77	14.13	16.85	20.02	23.73
	25	5.34	6.70	8.29	10.14	12.27	14.75	17.61	20.95	
	20	5.51	6.93	8.60	10.54	12.78	15.39	18.42		
	15	5.67	7.16	8.90	10.94	13.31	16.07			
10	5.82	7.38	9.21	11.36	13.87					
Input Power	65				6.53	6.80	7.05	7.29	7.50	7.70
	60			5.64	5.90	6.15	6.39	6.61	6.82	7.01
	55	4.62	4.87	5.12	5.36	5.60	5.82	6.03	6.23	6.41
	50	4.21	4.44	4.67	4.90	5.12	5.33	5.53	5.72	5.90
	45	3.86	4.07	4.28	4.49	4.70	4.90	5.09	5.27	5.44
	40	3.55	3.75	3.94	4.13	4.33	4.51	4.70	4.87	5.04
	35	3.27	3.44	3.62	3.80	3.98	4.16	4.33	4.50	4.67
	30	2.99	3.15	3.31	3.48	3.65	3.82	3.98	4.15	4.31
	25	2.71	2.85	2.99	3.15	3.31	3.47	3.63	3.80	
	20	2.40	2.52	2.66	2.80	2.95	3.11	3.26		
	15	2.05	2.16	2.28	2.41	2.56	2.71			
10	1.65	1.74	1.85	1.98	2.11					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表 Performance Matrix Table

XR110B-D1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				7.85	9.58	11.61	13.99	16.80	20.15
	60			6.93	8.51	10.35	12.49	15.00	17.95	21.43
	55	4.81	6.03	7.47	9.14	11.08	13.33	15.96	19.04	22.67
	50	5.15	6.45	7.96	9.73	11.77	14.13	16.88	20.10	23.88
	45	5.46	6.83	8.43	10.28	12.43	14.91	17.78	21.13	25.07
	40	5.75	7.19	8.87	10.81	13.06	15.66	18.67	22.17	26.27
	35	6.02	7.53	9.28	11.32	13.68	16.40	19.55	23.21	27.50
	30	6.26	7.84	9.68	11.82	14.29	17.14	20.44	24.29	28.79
	25	6.48	8.13	10.06	12.30	14.89	17.89	21.37	25.42	
	20	6.69	8.41	10.43	12.78	15.51	18.67	22.34		
	15	6.88	8.68	10.80	13.27	16.15	19.50			
10	7.06	8.95	11.18	13.79	16.83					
Input Power	65				7.99	8.31	8.62	8.91	9.18	9.42
	60			6.90	7.22	7.52	7.81	8.09	8.34	8.57
	55	5.65	5.96	6.26	6.56	6.84	7.12	7.38	7.62	7.84
	50	5.15	5.43	5.71	5.99	6.26	6.52	6.76	6.99	7.21
	45	4.72	4.98	5.24	5.50	5.75	5.99	6.23	6.45	6.66
	40	4.35	4.58	4.82	5.05	5.29	5.52	5.74	5.96	6.16
	35	4.00	4.21	4.43	4.65	4.87	5.09	5.30	5.51	5.71
	30	3.66	3.85	4.05	4.25	4.46	4.67	4.87	5.08	5.27
	25	3.31	3.48	3.66	3.85	4.05	4.24	4.44	4.64	
	20	2.94	3.09	3.25	3.42	3.61	3.80	3.99		
	15	2.51	2.64	2.79	2.95	3.13	3.31			
10	2.02	2.13	2.27	2.42	2.58					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR125B-D1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				8.93	10.90	13.21	15.93	19.13	22.94
	60			7.89	9.69	11.78	14.22	17.07	20.43	24.40
	55	5.47	6.87	8.50	10.40	12.61	15.18	18.17	21.67	25.81
	50	5.86	7.34	9.07	11.07	13.40	16.09	19.22	22.88	27.18
	45	6.22	7.78	9.60	11.71	14.15	16.97	20.24	24.06	28.54
	40	6.55	8.19	10.10	12.31	14.87	17.83	21.25	25.23	29.90
	35	6.85	8.57	10.57	12.89	15.57	18.67	22.25	26.42	31.31
	30	7.12	8.92	11.02	13.45	16.26	19.51	23.27	27.65	32.77
	25	7.38	9.26	11.45	14.00	16.95	20.37	24.33	28.93	
	20	7.61	9.57	11.87	14.55	17.66	21.26	25.44		
	15	7.83	9.88	12.30	15.11	18.39	22.19			
10	8.04	10.19	12.72	15.69	19.16					
Input Power	65				8.98	9.35	9.70	10.02	10.32	10.59
	60			7.76	8.12	8.46	8.79	9.09	9.38	9.64
	55	6.35	6.70	7.04	7.37	7.70	8.00	8.30	8.57	8.82
	50	5.79	6.11	6.43	6.74	7.04	7.33	7.61	7.87	8.11
	45	5.31	5.60	5.89	6.18	6.46	6.74	7.00	7.25	7.49
	40	4.89	5.15	5.42	5.68	5.95	6.21	6.46	6.70	6.93
	35	4.50	4.73	4.98	5.23	5.47	5.72	5.96	6.20	6.42
	30	4.12	4.33	4.55	4.78	5.01	5.25	5.48	5.71	5.93
	25	3.73	3.92	4.12	4.33	4.55	4.77	5.00	5.22	
	20	3.30	3.47	3.66	3.85	4.06	4.27	4.49		
	15	2.82	2.97	3.14	3.32	3.52	3.72			
10	2.27	2.40	2.55	2.72	2.90					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表 Performance Matrix Table

XR135B-D1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				9.66	11.79	14.29	17.22	20.69	24.81
	60			8.54	10.48	12.74	15.38	18.47	22.10	26.39
	55	5.92	7.43	9.19	11.25	13.64	16.42	19.65	23.44	27.91
	50	6.34	7.94	9.81	11.97	14.49	17.40	20.79	24.75	29.40
	45	6.73	8.41	10.38	12.66	15.30	18.36	21.90	26.02	30.87
	40	7.08	8.86	10.92	13.32	16.08	19.28	22.98	27.29	32.34
	35	7.41	9.27	11.43	13.94	16.84	20.19	24.07	28.58	33.86
	30	7.71	9.65	11.92	14.55	17.59	21.10	25.17	29.91	35.44
	25	7.98	10.01	12.39	15.14	18.34	22.03	26.31	31.30	
	20	8.23	10.36	12.84	15.74	19.10	22.99	27.51		
	15	8.47	10.69	13.30	16.35	19.89	24.01			
10	8.69	11.02	13.76	16.97	20.72					
Input Power	65				9.60	9.99	10.36	10.71	11.03	11.32
	60			8.29	8.67	9.04	9.39	9.72	10.03	10.30
	55	6.79	7.16	7.53	7.88	8.23	8.56	8.87	9.16	9.43
	50	6.19	6.53	6.87	7.20	7.52	7.83	8.13	8.41	8.67
	45	5.68	5.99	6.30	6.61	6.91	7.20	7.48	7.75	8.00
	40	5.23	5.51	5.79	6.08	6.36	6.64	6.91	7.16	7.41
	35	4.81	5.06	5.32	5.59	5.85	6.11	6.37	6.62	6.86
	30	4.40	4.63	4.87	5.11	5.36	5.61	5.86	6.10	6.34
	25	3.98	4.19	4.40	4.63	4.86	5.10	5.34	5.58	
	20	3.53	3.71	3.91	4.12	4.34	4.57	4.80		
	15	3.02	3.18	3.36	3.55	3.76	3.98			
10	2.42	2.56	2.72	2.90	3.10					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表 Performance Matrix Table

XR162B-D1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				11.63	14.19	17.20	20.73	24.90	29.85
	60			10.28	12.61	15.33	18.51	22.22	26.59	31.76
	55	7.12	8.94	11.06	13.54	16.41	19.75	23.65	28.21	33.59
	50	7.63	9.55	11.80	14.41	17.44	20.94	25.02	29.78	35.38
	45	8.10	10.12	12.49	15.24	18.41	22.09	26.35	31.32	37.14
	40	8.52	10.66	13.14	16.02	19.35	23.20	27.66	32.84	38.92
	35	8.92	11.15	13.76	16.78	20.27	24.30	28.97	34.39	40.75
	30	9.27	11.61	14.34	17.51	21.17	25.40	30.29	35.99	42.65
	25	9.60	12.05	14.91	18.22	22.07	26.51	31.67	37.66	
	20	9.91	12.46	15.46	18.94	22.98	27.67	33.11		
	15	10.19	12.86	16.00	19.67	23.93	28.89			
10	10.46	13.26	16.56	20.43	24.94					
Input Power	65				11.65	12.12	12.57	13.00	13.38	13.74
	60			10.06	10.52	10.97	11.39	11.79	12.16	12.50
	55	8.24	8.69	9.13	9.56	9.98	10.38	10.76	11.11	11.44
	50	7.51	7.93	8.34	8.74	9.13	9.51	9.86	10.20	10.52
	45	6.89	7.27	7.64	8.02	8.38	8.74	9.08	9.41	9.71
	40	6.34	6.68	7.03	7.37	7.72	8.05	8.38	8.69	8.99
	35	5.83	6.14	6.46	6.78	7.10	7.42	7.73	8.03	8.33
	30	5.34	5.62	5.90	6.20	6.50	6.81	7.11	7.40	7.69
	25	4.83	5.08	5.34	5.62	5.90	6.19	6.48	6.77	
	20	4.28	4.50	4.74	5.00	5.26	5.54	5.82		
	15	3.66	3.85	4.07	4.31	4.56	4.83			
10	2.94	3.11	3.30	3.52	3.76					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表 Performance Matrix Table

XR190B-D1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				13.52	16.50	20.00	24.10	28.95	34.71
	60			11.95	14.66	17.83	21.52	25.84	30.92	36.93
	55	8.28	10.39	12.86	15.74	19.09	22.97	27.50	32.81	39.06
	50	8.87	11.11	13.72	16.76	20.28	24.35	29.09	34.63	41.14
	45	9.41	11.77	14.53	17.72	21.41	25.69	30.64	36.42	43.19
	40	9.91	12.39	15.28	18.63	22.51	26.98	32.16	38.19	45.26
	35	10.37	12.97	16.00	19.51	23.57	28.26	33.68	39.99	47.38
	30	10.78	13.50	16.68	20.36	24.62	29.53	35.23	41.85	49.60
	25	11.17	14.01	17.33	21.19	25.66	30.83	36.82	43.80	
	20	11.52	14.49	17.97	22.03	26.73	32.18	38.50		
	15	11.85	14.96	18.61	22.87	27.83	33.59			
10	12.17	15.42	19.26	23.75	29.00					
Input Power	65				13.41	13.96	14.48	14.97	15.41	15.82
	60			11.59	12.12	12.63	13.12	13.58	14.01	14.40
	55	9.49	10.01	10.52	11.01	11.50	11.96	12.39	12.80	13.17
	50	8.65	9.13	9.60	10.06	10.51	10.95	11.36	11.75	12.11
	45	7.94	8.37	8.80	9.23	9.65	10.06	10.46	10.83	11.18
	40	7.30	7.69	8.09	8.49	8.89	9.27	9.65	10.01	10.35
	35	6.72	7.07	7.44	7.80	8.18	8.54	8.90	9.25	9.59
	30	6.15	6.47	6.80	7.14	7.49	7.84	8.19	8.53	8.86
	25	5.56	5.85	6.15	6.47	6.80	7.13	7.46	7.80	
	20	4.93	5.18	5.46	5.75	6.06	6.38	6.70		
	15	4.22	4.44	4.69	4.96	5.25	5.56			
10	3.39	3.58	3.81	4.06	4.34					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表 Performance Matrix Table

XR215B-D1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				15.41	18.81	22.79	27.47	32.99	39.56
	60			13.62	16.71	20.32	24.53	29.45	35.24	42.09
	55	9.44	11.84	14.66	17.94	21.75	26.18	31.34	37.38	44.52
	50	10.11	12.66	15.64	19.10	23.11	27.75	33.15	39.46	46.88
	45	10.73	13.42	16.55	20.19	24.40	29.27	34.92	41.50	49.22
	40	11.29	14.12	17.42	21.23	25.65	30.75	36.65	43.52	51.58
	35	11.81	14.78	18.23	22.23	26.86	32.20	38.38	45.58	54.00
	30	12.29	15.39	19.01	23.20	28.05	33.65	40.14	47.69	56.52
	25	12.72	15.96	19.75	24.15	29.24	35.13	41.96	49.91	
	20	13.13	16.51	20.48	25.10	30.46	36.67	43.87		
	15	13.50	17.05	21.21	26.07	31.72	38.28			
10	13.86	17.57	21.95	27.07	33.05					
Input Power	65				15.39	16.02	16.61	17.17	17.68	18.15
	60			13.29	13.90	14.49	15.05	15.58	16.07	16.51
	55	10.88	11.48	12.06	12.63	13.19	13.71	14.21	14.68	15.11
	50	9.93	10.47	11.01	11.54	12.06	12.56	13.03	13.48	13.89
	45	9.10	9.60	10.10	10.59	11.07	11.54	12.00	12.43	12.83
	40	8.37	8.83	9.28	9.74	10.19	10.64	11.07	11.48	11.88
	35	7.70	8.11	8.53	8.95	9.38	9.80	10.21	10.61	11.00
	30	7.05	7.42	7.80	8.19	8.59	8.99	9.39	9.78	10.16
	25	6.38	6.71	7.06	7.42	7.80	8.18	8.56	8.94	
	20	5.66	5.95	6.26	6.60	6.95	7.32	7.69		
	15	4.84	5.09	5.38	5.69	6.02	6.38			
10	3.88	4.11	4.37	4.66	4.97					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表 Performance Matrix Table

XR230B-D1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				16.40	20.02	24.26	29.24	35.12	42.11
	60			14.49	17.79	21.63	26.11	31.35	37.51	44.80
	55	10.05	12.61	15.60	19.09	23.15	27.86	33.36	39.79	47.39
	50	10.76	13.47	16.64	20.33	24.60	29.54	35.29	42.01	49.90
	45	11.42	14.28	17.62	21.49	25.97	31.16	37.17	44.17	52.39
	40	12.02	15.03	18.54	22.60	27.30	32.73	39.01	46.33	54.90
	35	12.58	15.73	19.41	23.67	28.59	34.28	40.86	48.51	57.48
	30	13.08	16.38	20.23	24.70	29.86	35.82	42.73	50.76	60.17
	25	13.54	16.99	21.03	25.71	31.13	37.40	44.67	53.12	
	20	13.97	17.58	21.80	26.72	32.42	39.03	46.70		
	15	14.37	18.14	22.57	27.75	33.76	40.75			
10	14.76	18.71	23.36	28.81	35.18					
Input Power	65				16.32	16.99	17.62	18.21	18.75	19.25
	60			14.09	14.75	15.37	15.96	16.52	17.04	17.51
	55	11.54	12.17	12.79	13.40	13.98	14.54	15.07	15.57	16.02
	50	10.53	11.11	11.68	12.24	12.79	13.32	13.82	14.29	14.73
	45	9.65	10.18	10.71	11.23	11.74	12.24	12.72	13.18	13.60
	40	8.88	9.36	9.84	10.33	10.81	11.28	11.74	12.18	12.59
	35	8.17	8.60	9.05	9.50	9.95	10.39	10.83	11.26	11.66
	30	7.48	7.87	8.27	8.69	9.11	9.54	9.96	10.37	10.77
	25	6.77	7.12	7.48	7.87	8.27	8.67	9.08	9.49	
	20	6.00	6.31	6.64	7.00	7.37	7.76	8.16		
	15	5.13	5.40	5.70	6.03	6.39	6.76			
10	4.12	4.36	4.63	4.94	5.27					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表 Performance Matrix Table

XR260B-D1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				18.58	22.68	27.48	33.12	39.79	47.71
	60			16.42	20.15	24.50	29.58	35.51	42.49	50.75
	55	11.38	14.28	17.68	21.63	26.23	31.57	37.79	45.08	53.68
	50	12.19	15.27	18.86	23.03	27.86	33.47	39.98	47.59	56.53
	45	12.94	16.18	19.96	24.35	29.43	35.30	42.11	50.04	59.36
	40	13.62	17.03	21.00	25.61	30.93	37.08	44.20	52.49	62.20
	35	14.25	17.82	21.98	26.81	32.39	38.83	46.29	54.96	65.12
	30	14.82	18.56	22.92	27.98	33.83	40.58	48.41	57.51	68.16
	25	15.34	19.25	23.82	29.12	35.27	42.37	50.60	60.18	
	20	15.83	19.91	24.70	30.27	36.73	44.22	52.91		
	15	16.28	20.56	25.57	31.43	38.25	46.17			
10	16.72	21.19	26.47	32.64	39.85					
Input Power	65				18.81	19.58	20.30	20.98	21.61	22.18
	60			16.24	16.99	17.71	18.40	19.04	19.64	20.19
	55	13.30	14.03	14.74	15.44	16.12	16.76	17.37	17.94	18.47
	50	12.13	12.80	13.46	14.11	14.74	15.35	15.93	16.47	16.98
	45	11.13	11.73	12.34	12.94	13.54	14.11	14.66	15.19	15.68
	40	10.24	10.79	11.35	11.90	12.46	13.00	13.53	14.04	14.51
	35	9.42	9.91	10.42	10.94	11.46	11.98	12.48	12.97	13.44
	30	8.62	9.07	9.53	10.01	10.50	10.99	11.48	11.95	12.42
	25	7.80	8.20	8.63	9.07	9.53	9.99	10.46	10.93	
	20	6.91	7.27	7.65	8.07	8.50	8.94	9.40		
	15	5.91	6.22	6.57	6.95	7.36	7.79			
10	4.75	5.02	5.34	5.69	6.08					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表 Performance Matrix Table

XR280B-D1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				19.80	24.16	29.28	35.29	42.39	50.82
	60			17.49	21.47	26.10	31.51	37.84	45.27	54.07
	55	12.13	15.22	18.83	23.05	27.94	33.63	40.26	48.03	57.19
	50	12.99	16.26	20.09	24.53	29.69	35.66	42.60	50.70	60.23
	45	13.78	17.24	21.27	25.94	31.35	37.61	44.86	53.32	63.24
	40	14.51	18.14	22.38	27.28	32.95	39.50	47.09	55.92	66.27
	35	15.18	18.98	23.42	28.56	34.51	41.37	49.31	58.55	69.37
	30	15.79	19.77	24.42	29.81	36.04	43.24	51.57	61.27	72.62
	25	16.35	20.51	25.38	31.03	37.57	45.14	53.91	64.12	
	20	16.87	21.22	26.31	32.25	39.13	47.11	56.37		
	15	17.35	21.90	27.25	33.49	40.75	49.18			
10	17.81	22.58	28.20	34.78	42.46					
Input Power	65				20.16	20.99	21.77	22.50	23.17	23.78
	60			17.41	18.22	18.99	19.72	20.42	21.06	21.64
	55	14.26	15.04	15.81	16.56	17.28	17.97	18.63	19.24	19.80
	50	13.01	13.72	14.43	15.12	15.80	16.45	17.08	17.66	18.21
	45	11.93	12.58	13.23	13.88	14.51	15.13	15.72	16.28	16.81
	40	10.97	11.57	12.16	12.76	13.36	13.94	14.50	15.05	15.56
	35	10.10	10.63	11.18	11.73	12.29	12.84	13.38	13.91	14.41
	30	9.24	9.72	10.22	10.74	11.26	11.78	12.30	12.82	13.31
	25	8.36	8.79	9.25	9.72	10.21	10.72	11.22	11.72	
	20	7.41	7.79	8.21	8.65	9.11	9.59	10.08		
	15	6.34	6.67	7.05	7.46	7.89	8.35			
10	5.09	5.38	5.72	6.10	6.52					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表 Performance Matrix Table

XR370B-D1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				26.92	32.86	39.81	47.99	57.64	69.11
	60			23.79	29.19	35.50	42.85	51.45	61.56	73.53
	55	16.49	20.69	25.61	31.34	38.00	45.73	54.75	65.31	77.77
	50	17.66	22.11	27.32	33.36	40.37	48.49	57.92	68.94	81.90
	45	18.74	23.44	28.92	35.28	42.63	51.14	61.00	72.50	85.99
	40	19.73	24.67	30.43	37.10	44.81	53.72	64.03	76.04	90.11
	35	20.64	25.82	31.85	38.84	46.92	56.26	67.06	79.62	94.33
	30	21.47	26.88	33.20	40.53	49.01	58.80	70.13	83.32	98.75
	25	22.23	27.89	34.51	42.19	51.09	61.38	73.31	87.19	
	20	22.93	28.85	35.78	43.85	53.21	64.06	76.65		
	15	23.59	29.78	37.05	45.54	55.41	66.88			
10	24.22	30.70	38.34	47.29	57.74					
Input Power	65				26.91	28.01	29.05	30.03	30.92	31.74
	60			23.24	24.32	25.35	26.33	27.25	28.10	28.88
	55	19.03	20.07	21.10	22.10	23.06	23.99	24.86	25.68	26.43
	50	17.36	18.31	19.26	20.19	21.09	21.96	22.79	23.57	24.30
	45	15.92	16.79	17.66	18.52	19.37	20.19	20.98	21.73	22.44
	40	14.65	15.44	16.23	17.03	17.83	18.60	19.36	20.08	20.77
	35	13.47	14.19	14.92	15.66	16.40	17.14	17.86	18.56	19.24
	30	12.33	12.97	13.64	14.33	15.03	15.73	16.42	17.11	17.77
	25	11.16	11.73	12.34	12.98	13.63	14.30	14.97	15.64	
	20	9.89	10.40	10.95	11.54	12.16	12.80	13.45		
	15	8.46	8.90	9.40	9.95	10.54	11.15			
10	6.79	7.18	7.64	8.14	8.70					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表 Performance Matrix Table

XR420B-D1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				30.73	37.51	45.45	54.78	65.80	78.90
	60			27.16	33.33	40.52	48.92	58.73	70.28	83.94
	55	18.83	23.62	29.23	35.78	43.38	52.21	62.50	74.56	88.78
	50	20.16	25.25	31.18	38.09	46.08	55.35	66.12	78.70	93.50
	45	21.40	26.76	33.01	40.27	48.67	58.38	69.64	82.76	98.17
	40	22.53	28.16	34.73	42.35	51.15	61.32	73.10	86.81	102.87
	35	23.56	29.47	36.36	44.34	53.57	64.22	76.55	90.90	107.69
	30	24.51	30.69	37.90	46.27	55.94	67.12	80.06	95.11	112.73
	25	25.38	31.84	39.39	48.17	58.32	70.07	83.69	99.53	
	20	26.18	32.94	40.85	50.06	60.74	73.13	87.50		
	15	26.93	34.00	42.30	51.99	63.26	76.35			
10	27.65	35.05	43.77	53.99	65.91					
Input Power	65				30.83	32.09	33.28	34.39	35.42	36.35
	60			26.62	27.85	29.03	30.15	31.21	32.19	33.08
	55	21.80	22.99	24.17	25.31	26.41	27.47	28.47	29.41	30.27
	50	19.88	20.98	22.06	23.12	24.16	25.15	26.11	27.00	27.83
	45	18.23	19.23	20.23	21.21	22.18	23.13	24.03	24.89	25.70
	40	16.78	17.68	18.59	19.51	20.42	21.31	22.17	23.00	23.79
	35	15.43	16.25	17.09	17.93	18.79	19.63	20.46	21.26	22.03
	30	14.13	14.86	15.63	16.41	17.21	18.01	18.81	19.59	20.35
	25	12.79	13.44	14.14	14.86	15.62	16.38	17.15	17.92	
	20	11.33	11.91	12.54	13.22	13.93	14.66	15.41		
	15	9.69	10.20	10.77	11.40	12.07	12.77			
10	7.78	8.23	8.75	9.33	9.96					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表 Performance Matrix Table

XR510B-D1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				37.64	45.94	55.67	67.10	80.59	96.63
	60			33.26	40.82	49.63	59.91	71.94	86.08	102.81
	55	23.06	28.93	35.81	43.82	53.13	63.94	76.55	91.32	108.74
	50	24.70	30.92	38.20	46.65	56.44	67.80	80.99	96.40	114.52
	45	26.21	32.77	40.44	49.33	59.61	71.50	85.29	101.37	120.24
	40	27.59	34.49	42.54	51.87	62.65	75.11	89.53	106.32	125.99
	35	28.86	36.10	44.53	54.31	65.61	78.66	93.76	111.33	131.90
	30	30.02	37.59	46.43	56.67	68.52	82.21	98.06	116.49	138.07
	25	31.08	39.00	48.25	58.99	71.43	85.82	102.50	121.91	
	20	32.07	40.34	50.03	61.31	74.40	89.57	107.17		
	15	32.99	41.64	51.81	63.67	77.48	93.51			
10	33.87	42.93	53.61	66.12	80.73					
Input Power	65				37.37	38.90	40.34	41.69	42.94	44.07
	60			32.27	33.76	35.19	36.55	37.83	39.02	40.10
	55	26.42	27.87	29.29	30.68	32.02	33.30	34.52	35.65	36.69
	50	24.10	25.43	26.74	28.03	29.28	30.49	31.65	32.73	33.74
	45	22.11	23.31	24.52	25.72	26.89	28.03	29.13	30.17	31.15
	40	20.34	21.43	22.54	23.65	24.75	25.83	26.88	27.89	28.84
	35	18.71	19.70	20.71	21.74	22.77	23.80	24.80	25.78	26.71
	30	17.13	18.02	18.94	19.89	20.86	21.84	22.80	23.75	24.67
	25	15.50	16.29	17.14	18.02	18.93	19.86	20.79	21.72	
	20	13.74	14.44	15.21	16.02	16.88	17.77	18.68		
	15	11.74	12.36	13.06	13.82	14.63	15.48			
10	9.43	9.97	10.60	11.31	12.08					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR22B-E1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				1.69	2.06	2.49	3.01	3.61	4.33
	60			1.49	1.83	2.22	2.68	3.22	3.86	4.61
	55	1.03	1.30	1.60	1.96	2.38	2.86	3.43	4.09	4.87
	50	1.11	1.39	1.71	2.09	2.53	3.04	3.63	4.32	5.13
	45	1.17	1.47	1.81	2.21	2.67	3.20	3.82	4.54	5.39
	40	1.24	1.55	1.91	2.32	2.81	3.36	4.01	4.76	5.64
	35	1.29	1.62	2.00	2.43	2.94	3.52	4.20	4.99	5.91
	30	1.34	1.68	2.08	2.54	3.07	3.68	4.39	5.22	6.19
	25	1.39	1.75	2.16	2.64	3.20	3.84	4.59	5.46	
	20	1.44	1.81	2.24	2.75	3.33	4.01	4.80		
	15	1.48	1.87	2.32	2.85	3.47	4.19			
10	1.52	1.92	2.40	2.96	3.62					
Input Power	65				1.99	2.07	2.14	2.22	2.28	2.34
	60			1.72	1.79	1.87	1.94	2.01	2.07	2.13
	55	1.40	1.48	1.56	1.63	1.70	1.77	1.83	1.89	1.95
	50	1.28	1.35	1.42	1.49	1.56	1.62	1.68	1.74	1.79
	45	1.17	1.24	1.30	1.37	1.43	1.49	1.55	1.60	1.66
	40	1.08	1.14	1.20	1.26	1.32	1.37	1.43	1.48	1.53
	35	0.99	1.05	1.10	1.16	1.21	1.26	1.32	1.37	1.42
	30	0.91	0.96	1.01	1.06	1.11	1.16	1.21	1.26	1.31
	25	0.82	0.87	0.91	0.96	1.01	1.06	1.11	1.15	
	20	0.73	0.77	0.81	0.85	0.90	0.94	0.99		
	15	0.62	0.66	0.69	0.73	0.78	0.82			
10	0.50	0.53	0.56	0.60	0.64					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR28B-E1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				1.96	2.40	2.90	3.50	4.20	5.04
	60			1.73	2.13	2.59	3.12	3.75	4.49	5.36
	55	1.20	1.51	1.87	2.29	2.77	3.33	3.99	4.76	5.67
	50	1.29	1.61	1.99	2.43	2.94	3.54	4.22	5.03	5.97
	45	1.37	1.71	2.11	2.57	3.11	3.73	4.45	5.29	6.27
	40	1.44	1.80	2.22	2.71	3.27	3.92	4.67	5.54	6.57
	35	1.51	1.88	2.32	2.83	3.42	4.10	4.89	5.81	6.88
	30	1.57	1.96	2.42	2.96	3.57	4.29	5.11	6.08	7.20
	25	1.62	2.03	2.52	3.08	3.73	4.48	5.35	6.36	
	20	1.67	2.10	2.61	3.20	3.88	4.67	5.59		
	15	1.72	2.17	2.70	3.32	4.04	4.88			
10	1.77	2.24	2.80	3.45	4.21					
Input Power	65				2.18	2.27	2.35	2.43	2.50	2.57
	60			1.88	1.97	2.05	2.13	2.21	2.28	2.34
	55	1.54	1.62	1.71	1.79	1.87	1.94	2.01	2.08	2.14
	50	1.41	1.48	1.56	1.63	1.71	1.78	1.85	1.91	1.97
	45	1.29	1.36	1.43	1.50	1.57	1.63	1.70	1.76	1.82
	40	1.19	1.25	1.31	1.38	1.44	1.51	1.57	1.63	1.68
	35	1.09	1.15	1.21	1.27	1.33	1.39	1.45	1.50	1.56
	30	1.00	1.05	1.10	1.16	1.22	1.27	1.33	1.38	1.44
	25	0.90	0.95	1.00	1.05	1.10	1.16	1.21	1.27	
	20	0.80	0.84	0.89	0.93	0.98	1.04	1.09		
	15	0.68	0.72	0.76	0.81	0.85	0.90			
10	0.55	0.58	0.62	0.66	0.70					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR32B-E1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				2.39	2.91	3.53	4.25	5.11	6.12
	60			2.11	2.59	3.15	3.80	4.56	5.45	6.52
	55	1.46	1.83	2.27	2.78	3.37	4.05	4.85	5.79	6.89
	50	1.57	1.96	2.42	2.96	3.58	4.30	5.13	6.11	7.26
	45	1.66	2.08	2.56	3.13	3.78	4.53	5.41	6.42	7.62
	40	1.75	2.19	2.70	3.29	3.97	4.76	5.67	6.74	7.98
	35	1.83	2.29	2.82	3.44	4.16	4.98	5.94	7.06	8.36
	30	1.90	2.38	2.94	3.59	4.34	5.21	6.21	7.38	8.75
	25	1.97	2.47	3.06	3.74	4.53	5.44	6.50	7.73	
	20	2.03	2.56	3.17	3.89	4.71	5.68	6.79		
	15	2.09	2.64	3.28	4.04	4.91	5.93			
10	2.15	2.72	3.40	4.19	5.12					
Input Power	65				2.58	2.68	2.78	2.88	2.96	3.04
	60			2.23	2.33	2.43	2.52	2.61	2.69	2.77
	55	1.82	1.92	2.02	2.12	2.21	2.30	2.38	2.46	2.53
	50	1.66	1.75	1.84	1.93	2.02	2.10	2.18	2.26	2.33
	45	1.52	1.61	1.69	1.77	1.85	1.93	2.01	2.08	2.15
	40	1.40	1.48	1.55	1.63	1.71	1.78	1.85	1.92	1.99
	35	1.29	1.36	1.43	1.50	1.57	1.64	1.71	1.78	1.84
	30	1.18	1.24	1.31	1.37	1.44	1.51	1.57	1.64	1.70
	25	1.07	1.12	1.18	1.24	1.31	1.37	1.43	1.50	
	20	0.95	1.00	1.05	1.11	1.16	1.23	1.29		
	15	0.81	0.85	0.90	0.95	1.01	1.07			
10	0.65	0.69	0.73	0.78	0.83					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR38B-E1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				2.72	3.31	4.02	4.84	5.81	6.97
	60			2.40	2.95	3.58	4.32	5.19	6.21	7.42
	55	1.66	2.09	2.58	3.16	3.83	4.61	5.52	6.59	7.85
	50	1.78	2.23	2.76	3.37	4.07	4.89	5.84	6.96	8.26
	45	1.89	2.36	2.92	3.56	4.30	5.16	6.15	7.31	8.68
	40	1.99	2.49	3.07	3.74	4.52	5.42	6.46	7.67	9.09
	35	2.08	2.60	3.21	3.92	4.73	5.68	6.77	8.03	9.52
	30	2.17	2.71	3.35	4.09	4.94	5.93	7.08	8.41	9.96
	25	2.24	2.81	3.48	4.26	5.15	6.19	7.40	8.80	
	20	2.31	2.91	3.61	4.42	5.37	6.46	7.73		
	15	2.38	3.00	3.74	4.59	5.59	6.75			
10	2.44	3.10	3.87	4.77	5.82					
Input Power	65				2.89	3.01	3.12	3.22	3.32	3.41
	60			2.50	2.61	2.72	2.83	2.93	3.02	3.10
	55	2.04	2.16	2.27	2.37	2.48	2.58	2.67	2.76	2.84
	50	1.86	1.97	2.07	2.17	2.26	2.36	2.45	2.53	2.61
	45	1.71	1.80	1.90	1.99	2.08	2.17	2.25	2.33	2.41
	40	1.57	1.66	1.74	1.83	1.91	2.00	2.08	2.16	2.23
	35	1.45	1.52	1.60	1.68	1.76	1.84	1.92	1.99	2.07
	30	1.32	1.39	1.46	1.54	1.61	1.69	1.76	1.84	1.91
	25	1.20	1.26	1.33	1.39	1.46	1.54	1.61	1.68	
	20	1.06	1.12	1.18	1.24	1.31	1.37	1.44		
	15	0.91	0.96	1.01	1.07	1.13	1.20			
10	0.73	0.77	0.82	0.87	0.93					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR45B-E1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				3.21	3.92	4.75	5.72	6.87	8.24
	60			2.84	3.48	4.23	5.11	6.13	7.34	8.76
	55	1.97	2.47	3.05	3.74	4.53	5.45	6.53	7.79	9.27
	50	2.11	2.64	3.26	3.98	4.81	5.78	6.90	8.22	9.76
	45	2.23	2.79	3.45	4.21	5.08	6.10	7.27	8.64	10.25
	40	2.35	2.94	3.63	4.42	5.34	6.40	7.63	9.06	10.74
	35	2.46	3.08	3.80	4.63	5.59	6.71	7.99	9.49	11.24
	30	2.56	3.20	3.96	4.83	5.84	7.01	8.36	9.93	11.77
	25	2.65	3.32	4.11	5.03	6.09	7.32	8.74	10.39	
	20	2.73	3.44	4.27	5.23	6.34	7.64	9.14		
	15	2.81	3.55	4.42	5.43	6.61	7.97			
10	2.89	3.66	4.57	5.64	6.88					
Input Power	65				3.38	3.52	3.65	3.77	3.89	3.99
	60			2.92	3.06	3.19	3.31	3.43	3.53	3.63
	55	2.39	2.52	2.65	2.78	2.90	3.02	3.13	3.23	3.32
	50	2.18	2.30	2.42	2.54	2.65	2.76	2.87	2.96	3.05
	45	2.00	2.11	2.22	2.33	2.43	2.54	2.64	2.73	2.82
	40	1.84	1.94	2.04	2.14	2.24	2.34	2.43	2.53	2.61
	35	1.69	1.78	1.88	1.97	2.06	2.15	2.25	2.33	2.42
	30	1.55	1.63	1.72	1.80	1.89	1.98	2.06	2.15	2.23
	25	1.40	1.48	1.55	1.63	1.71	1.80	1.88	1.97	
	20	1.24	1.31	1.38	1.45	1.53	1.61	1.69		
	15	1.06	1.12	1.18	1.25	1.32	1.40			
10	0.85	0.90	0.96	1.02	1.09					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR52B-E1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				3.73	4.55	5.52	6.65	7.99	9.58
	60			3.30	4.05	4.92	5.94	7.13	8.53	10.19
	55	2.29	2.87	3.55	4.34	5.27	6.34	7.59	9.05	10.78
	50	2.45	3.06	3.79	4.62	5.59	6.72	8.03	9.55	11.35
	45	2.60	3.25	4.01	4.89	5.91	7.09	8.45	10.05	11.92
	40	2.73	3.42	4.22	5.14	6.21	7.44	8.87	10.54	12.49
	35	2.86	3.58	4.41	5.38	6.50	7.80	9.29	11.03	13.07
	30	2.98	3.73	4.60	5.62	6.79	8.15	9.72	11.55	13.68
	25	3.08	3.87	4.78	5.85	7.08	8.51	10.16	12.08	
	20	3.18	4.00	4.96	6.08	7.37	8.88	10.62		
	15	3.27	4.13	5.13	6.31	7.68	9.27			
10	3.36	4.25	5.31	6.55	8.00					
Input Power	65				3.87	4.03	4.18	4.32	4.45	4.57
	60			3.35	3.50	3.65	3.79	3.92	4.05	4.16
	55	2.74	2.89	3.04	3.18	3.32	3.45	3.58	3.70	3.80
	50	2.50	2.64	2.77	2.91	3.04	3.16	3.28	3.39	3.50
	45	2.29	2.42	2.54	2.67	2.79	2.91	3.02	3.13	3.23
	40	2.11	2.22	2.34	2.45	2.57	2.68	2.79	2.89	2.99
	35	1.94	2.04	2.15	2.25	2.36	2.47	2.57	2.67	2.77
	30	1.78	1.87	1.96	2.06	2.16	2.26	2.36	2.46	2.56
	25	1.61	1.69	1.78	1.87	1.96	2.06	2.16	2.25	
	20	1.42	1.50	1.58	1.66	1.75	1.84	1.94		
	15	1.22	1.28	1.35	1.43	1.52	1.61			
10	0.98	1.03	1.10	1.17	1.25					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR63B-E1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				4.52	5.51	6.68	8.05	9.67	11.60
	60			3.99	4.90	5.96	7.19	8.63	10.33	12.34
	55	2.77	3.47	4.30	5.26	6.38	7.67	9.19	10.96	13.05
	50	2.96	3.71	4.58	5.60	6.77	8.14	9.72	11.57	13.74
	45	3.14	3.93	4.85	5.92	7.15	8.58	10.24	12.16	14.43
	40	3.31	4.14	5.11	6.22	7.52	9.01	10.74	12.76	15.12
	35	3.46	4.33	5.34	6.52	7.87	9.44	11.25	13.36	15.83
	30	3.60	4.51	5.57	6.80	8.22	9.87	11.77	13.98	16.57
	25	3.73	4.68	5.79	7.08	8.57	10.30	12.30	14.63	
	20	3.85	4.84	6.00	7.36	8.93	10.75	12.86		
	15	3.96	5.00	6.22	7.64	9.30	11.22			
10	4.06	5.15	6.43	7.93	9.69					
Input Power	65				4.60	4.79	4.97	5.13	5.29	5.43
	60			3.97	4.16	4.33	4.50	4.66	4.81	4.94
	55	3.25	3.43	3.61	3.78	3.94	4.10	4.25	4.39	4.52
	50	2.97	3.13	3.29	3.45	3.61	3.76	3.90	4.03	4.15
	45	2.72	2.87	3.02	3.17	3.31	3.45	3.59	3.72	3.84
	40	2.50	2.64	2.78	2.91	3.05	3.18	3.31	3.43	3.55
	35	2.30	2.43	2.55	2.68	2.80	2.93	3.05	3.17	3.29
	30	2.11	2.22	2.33	2.45	2.57	2.69	2.81	2.92	3.04
	25	1.91	2.01	2.11	2.22	2.33	2.45	2.56	2.67	
	20	1.69	1.78	1.87	1.97	2.08	2.19	2.30		
	15	1.45	1.52	1.61	1.70	1.80	1.91			
10	1.16	1.23	1.31	1.39	1.49					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表 Performance Matrix Table

XR72B-E1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				5.15	6.29	7.62	9.18	11.03	13.22
	60			4.55	5.58	6.79	8.20	9.84	11.78	14.06
	55	3.15	3.96	4.90	5.99	7.27	8.75	10.47	12.49	14.88
	50	3.38	4.23	5.23	6.38	7.72	9.27	11.08	13.19	15.67
	45	3.59	4.48	5.53	6.75	8.15	9.78	11.67	13.87	16.45
	40	3.77	4.72	5.82	7.10	8.57	10.27	12.25	14.55	17.24
	35	3.95	4.94	6.09	7.43	8.98	10.76	12.83	15.23	18.04
	30	4.11	5.14	6.35	7.75	9.37	11.25	13.42	15.94	18.89
	25	4.25	5.34	6.60	8.07	9.77	11.74	14.02	16.68	
	20	4.39	5.52	6.84	8.39	10.18	12.25	14.66		
	15	4.51	5.70	7.09	8.71	10.60	12.79			
10	4.63	5.87	7.33	9.05	11.04					
Input Power	65				5.15	5.36	5.56	5.75	5.92	6.08
	60			4.45	4.66	4.85	5.04	5.22	5.38	5.53
	55	3.64	3.84	4.04	4.23	4.42	4.59	4.76	4.92	5.06
	50	3.32	3.51	3.69	3.87	4.04	4.21	4.36	4.51	4.65
	45	3.05	3.21	3.38	3.55	3.71	3.87	4.02	4.16	4.30
	40	2.80	2.96	3.11	3.26	3.41	3.56	3.71	3.85	3.98
	35	2.58	2.72	2.86	3.00	3.14	3.28	3.42	3.55	3.68
	30	2.36	2.48	2.61	2.74	2.88	3.01	3.14	3.28	3.40
	25	2.14	2.25	2.36	2.48	2.61	2.74	2.87	3.00	
	20	1.89	1.99	2.10	2.21	2.33	2.45	2.58		
	15	1.62	1.70	1.80	1.91	2.02	2.13			
10	1.30	1.38	1.46	1.56	1.67					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR91B-E1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				6.47	7.89	9.57	11.53	13.85	16.61
	60			5.72	7.01	8.53	10.30	12.36	14.79	17.67
	55	3.96	4.97	6.15	7.53	9.13	10.99	13.15	15.69	18.69
	50	4.24	5.31	6.56	8.02	9.70	11.65	13.92	16.56	19.68
	45	4.50	5.63	6.95	8.48	10.24	12.29	14.66	17.42	20.66
	40	4.74	5.93	7.31	8.91	10.77	12.91	15.38	18.27	21.65
	35	4.96	6.20	7.65	9.33	11.27	13.52	16.11	19.13	22.67
	30	5.16	6.46	7.98	9.74	11.77	14.13	16.85	20.02	23.73
	25	5.34	6.70	8.29	10.14	12.27	14.75	17.61	20.95	
	20	5.51	6.93	8.60	10.54	12.78	15.39	18.42		
	15	5.67	7.16	8.90	10.94	13.31	16.07			
10	5.82	7.38	9.21	11.36	13.87					
Input Power	65				6.53	6.80	7.05	7.29	7.50	7.70
	60			5.64	5.90	6.15	6.39	6.61	6.82	7.01
	55	4.62	4.87	5.12	5.36	5.60	5.82	6.03	6.23	6.41
	50	4.21	4.44	4.67	4.90	5.12	5.33	5.53	5.72	5.90
	45	3.86	4.07	4.28	4.49	4.70	4.90	5.09	5.27	5.44
	40	3.55	3.75	3.94	4.13	4.33	4.51	4.70	4.87	5.04
	35	3.27	3.44	3.62	3.80	3.98	4.16	4.33	4.50	4.67
	30	2.99	3.15	3.31	3.48	3.65	3.82	3.98	4.15	4.31
	25	2.71	2.85	2.99	3.15	3.31	3.47	3.63	3.80	
	20	2.40	2.52	2.66	2.80	2.95	3.11	3.26		
	15	2.05	2.16	2.28	2.41	2.56	2.71			
10	1.65	1.74	1.85	1.98	2.11					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR110B-E1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				7.85	9.58	11.61	13.99	16.80	20.15
	60			6.93	8.51	10.35	12.49	15.00	17.95	21.43
	55	4.81	6.03	7.47	9.14	11.08	13.33	15.96	19.04	22.67
	50	5.15	6.45	7.96	9.73	11.77	14.13	16.88	20.10	23.88
	45	5.46	6.83	8.43	10.28	12.43	14.91	17.78	21.13	25.07
	40	5.75	7.19	8.87	10.81	13.06	15.66	18.67	22.17	26.27
	35	6.02	7.53	9.28	11.32	13.68	16.40	19.55	23.21	27.50
	30	6.26	7.84	9.68	11.82	14.29	17.14	20.44	24.29	28.79
	25	6.48	8.13	10.06	12.30	14.89	17.89	21.37	25.42	
	20	6.69	8.41	10.43	12.78	15.51	18.67	22.34		
	15	6.88	8.68	10.80	13.27	16.15	19.50			
10	7.06	8.95	11.18	13.79	16.83					
Input Power	65				7.99	8.31	8.62	8.91	9.18	9.42
	60			6.90	7.22	7.52	7.81	8.09	8.34	8.57
	55	5.65	5.96	6.26	6.56	6.84	7.12	7.38	7.62	7.84
	50	5.15	5.43	5.71	5.99	6.26	6.52	6.76	6.99	7.21
	45	4.72	4.98	5.24	5.50	5.75	5.99	6.23	6.45	6.66
	40	4.35	4.58	4.82	5.05	5.29	5.52	5.74	5.96	6.16
	35	4.00	4.21	4.43	4.65	4.87	5.09	5.30	5.51	5.71
	30	3.66	3.85	4.05	4.25	4.46	4.67	4.87	5.08	5.27
	25	3.31	3.48	3.66	3.85	4.05	4.24	4.44	4.64	
	20	2.94	3.09	3.25	3.42	3.61	3.80	3.99		
	15	2.51	2.64	2.79	2.95	3.13	3.31			
10	2.02	2.13	2.27	2.42	2.58					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR125B-E1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				8.93	10.90	13.21	15.93	19.13	22.94
	60			7.89	9.69	11.78	14.22	17.07	20.43	24.40
	55	5.47	6.87	8.50	10.40	12.61	15.18	18.17	21.67	25.81
	50	5.86	7.34	9.07	11.07	13.40	16.09	19.22	22.88	27.18
	45	6.22	7.78	9.60	11.71	14.15	16.97	20.24	24.06	28.54
	40	6.55	8.19	10.10	12.31	14.87	17.83	21.25	25.23	29.90
	35	6.85	8.57	10.57	12.89	15.57	18.67	22.25	26.42	31.31
	30	7.12	8.92	11.02	13.45	16.26	19.51	23.27	27.65	32.77
	25	7.38	9.26	11.45	14.00	16.95	20.37	24.33	28.93	
	20	7.61	9.57	11.87	14.55	17.66	21.26	25.44		
	15	7.83	9.88	12.30	15.11	18.39	22.19			
10	8.04	10.19	12.72	15.69	19.16					
Input Power	65				8.98	9.35	9.70	10.02	10.32	10.59
	60			7.76	8.12	8.46	8.79	9.09	9.38	9.64
	55	6.35	6.70	7.04	7.37	7.70	8.00	8.30	8.57	8.82
	50	5.79	6.11	6.43	6.74	7.04	7.33	7.61	7.87	8.11
	45	5.31	5.60	5.89	6.18	6.46	6.74	7.00	7.25	7.49
	40	4.89	5.15	5.42	5.68	5.95	6.21	6.46	6.70	6.93
	35	4.50	4.73	4.98	5.23	5.47	5.72	5.96	6.20	6.42
	30	4.12	4.33	4.55	4.78	5.01	5.25	5.48	5.71	5.93
	25	3.73	3.92	4.12	4.33	4.55	4.77	5.00	5.22	
	20	3.30	3.47	3.66	3.85	4.06	4.27	4.49		
	15	2.82	2.97	3.14	3.32	3.52	3.72			
10	2.27	2.40	2.55	2.72	2.90					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR135B-E1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				9.66	11.79	14.29	17.22	20.69	24.81
	60			8.54	10.48	12.74	15.38	18.47	22.10	26.39
	55	5.92	7.43	9.19	11.25	13.64	16.42	19.65	23.44	27.91
	50	6.34	7.94	9.81	11.97	14.49	17.40	20.79	24.75	29.40
	45	6.73	8.41	10.38	12.66	15.30	18.36	21.90	26.02	30.87
	40	7.08	8.86	10.92	13.32	16.08	19.28	22.98	27.29	32.34
	35	7.41	9.27	11.43	13.94	16.84	20.19	24.07	28.58	33.86
	30	7.71	9.65	11.92	14.55	17.59	21.10	25.17	29.91	35.44
	25	7.98	10.01	12.39	15.14	18.34	22.03	26.31	31.30	
	20	8.23	10.36	12.84	15.74	19.10	22.99	27.51		
	15	8.47	10.69	13.30	16.35	19.89	24.01			
10	8.69	11.02	13.76	16.97	20.72					
Input Power	65				9.60	9.99	10.36	10.71	11.03	11.32
	60			8.29	8.67	9.04	9.39	9.72	10.03	10.30
	55	6.79	7.16	7.53	7.88	8.23	8.56	8.87	9.16	9.43
	50	6.19	6.53	6.87	7.20	7.52	7.83	8.13	8.41	8.67
	45	5.68	5.99	6.30	6.61	6.91	7.20	7.48	7.75	8.00
	40	5.23	5.51	5.79	6.08	6.36	6.64	6.91	7.16	7.41
	35	4.81	5.06	5.32	5.59	5.85	6.11	6.37	6.62	6.86
	30	4.40	4.63	4.87	5.11	5.36	5.61	5.86	6.10	6.34
	25	3.98	4.19	4.40	4.63	4.86	5.10	5.34	5.58	
	20	3.53	3.71	3.91	4.12	4.34	4.57	4.80		
	15	3.02	3.18	3.36	3.55	3.76	3.98			
10	2.42	2.56	2.72	2.90	3.10					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR162B-E1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				11.63	14.19	17.20	20.73	24.90	29.85
	60			10.28	12.61	15.33	18.51	22.22	26.59	31.76
	55	7.12	8.94	11.06	13.54	16.41	19.75	23.65	28.21	33.59
	50	7.63	9.55	11.80	14.41	17.44	20.94	25.02	29.78	35.38
	45	8.10	10.12	12.49	15.24	18.41	22.09	26.35	31.32	37.14
	40	8.52	10.66	13.14	16.02	19.35	23.20	27.66	32.84	38.92
	35	8.92	11.15	13.76	16.78	20.27	24.30	28.97	34.39	40.75
	30	9.27	11.61	14.34	17.51	21.17	25.40	30.29	35.99	42.65
	25	9.60	12.05	14.91	18.22	22.07	26.51	31.67	37.66	
	20	9.91	12.46	15.46	18.94	22.98	27.67	33.11		
	15	10.19	12.86	16.00	19.67	23.93	28.89			
10	10.46	13.26	16.56	20.43	24.94					
Input Power	65				11.65	12.12	12.57	13.00	13.38	13.74
	60			10.06	10.52	10.97	11.39	11.79	12.16	12.50
	55	8.24	8.69	9.13	9.56	9.98	10.38	10.76	11.11	11.44
	50	7.51	7.93	8.34	8.74	9.13	9.51	9.86	10.20	10.52
	45	6.89	7.27	7.64	8.02	8.38	8.74	9.08	9.41	9.71
	40	6.34	6.68	7.03	7.37	7.72	8.05	8.38	8.69	8.99
	35	5.83	6.14	6.46	6.78	7.10	7.42	7.73	8.03	8.33
	30	5.34	5.62	5.90	6.20	6.50	6.81	7.11	7.40	7.69
	25	4.83	5.08	5.34	5.62	5.90	6.19	6.48	6.77	
	20	4.28	4.50	4.74	5.00	5.26	5.54	5.82		
	15	3.66	3.85	4.07	4.31	4.56	4.83			
10	2.94	3.11	3.30	3.52	3.76					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR190B-E1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				13.52	16.50	20.00	24.10	28.95	34.71
	60			11.95	14.66	17.83	21.52	25.84	30.92	36.93
	55	8.28	10.39	12.86	15.74	19.09	22.97	27.50	32.81	39.06
	50	8.87	11.11	13.72	16.76	20.28	24.35	29.09	34.63	41.14
	45	9.41	11.77	14.53	17.72	21.41	25.69	30.64	36.42	43.19
	40	9.91	12.39	15.28	18.63	22.51	26.98	32.16	38.19	45.26
	35	10.37	12.97	16.00	19.51	23.57	28.26	33.68	39.99	47.38
	30	10.78	13.50	16.68	20.36	24.62	29.53	35.23	41.85	49.60
	25	11.17	14.01	17.33	21.19	25.66	30.83	36.82	43.80	
	20	11.52	14.49	17.97	22.03	26.73	32.18	38.50		
	15	11.85	14.96	18.61	22.87	27.83	33.59			
10	12.17	15.42	19.26	23.75	29.00					
Input Power	65				13.41	13.96	14.48	14.97	15.41	15.82
	60			11.59	12.12	12.63	13.12	13.58	14.01	14.40
	55	9.49	10.01	10.52	11.01	11.50	11.96	12.39	12.80	13.17
	50	8.65	9.13	9.60	10.06	10.51	10.95	11.36	11.75	12.11
	45	7.94	8.37	8.80	9.23	9.65	10.06	10.46	10.83	11.18
	40	7.30	7.69	8.09	8.49	8.89	9.27	9.65	10.01	10.35
	35	6.72	7.07	7.44	7.80	8.18	8.54	8.90	9.25	9.59
	30	6.15	6.47	6.80	7.14	7.49	7.84	8.19	8.53	8.86
	25	5.56	5.85	6.15	6.47	6.80	7.13	7.46	7.80	
	20	4.93	5.18	5.46	5.75	6.06	6.38	6.70		
	15	4.22	4.44	4.69	4.96	5.25	5.56			
10	3.39	3.58	3.81	4.06	4.34					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR215B-E1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				15.41	18.81	22.79	27.47	32.99	39.56
	60			13.62	16.71	20.32	24.53	29.45	35.24	42.09
	55	9.44	11.84	14.66	17.94	21.75	26.18	31.34	37.38	44.52
	50	10.11	12.66	15.64	19.10	23.11	27.75	33.15	39.46	46.88
	45	10.73	13.42	16.55	20.19	24.40	29.27	34.92	41.50	49.22
	40	11.29	14.12	17.42	21.23	25.65	30.75	36.65	43.52	51.58
	35	11.81	14.78	18.23	22.23	26.86	32.20	38.38	45.58	54.00
	30	12.29	15.39	19.01	23.20	28.05	33.65	40.14	47.69	56.52
	25	12.72	15.96	19.75	24.15	29.24	35.13	41.96	49.91	
	20	13.13	16.51	20.48	25.10	30.46	36.67	43.87		
	15	13.50	17.05	21.21	26.07	31.72	38.28			
10	13.86	17.57	21.95	27.07	33.05					
Input Power	65				15.39	16.02	16.61	17.17	17.68	18.15
	60			13.29	13.90	14.49	15.05	15.58	16.07	16.51
	55	10.88	11.48	12.06	12.63	13.19	13.71	14.21	14.68	15.11
	50	9.93	10.47	11.01	11.54	12.06	12.56	13.03	13.48	13.89
	45	9.10	9.60	10.10	10.59	11.07	11.54	12.00	12.43	12.83
	40	8.37	8.83	9.28	9.74	10.19	10.64	11.07	11.48	11.88
	35	7.70	8.11	8.53	8.95	9.38	9.80	10.21	10.61	11.00
	30	7.05	7.42	7.80	8.19	8.59	8.99	9.39	9.78	10.16
	25	6.38	6.71	7.06	7.42	7.80	8.18	8.56	8.94	
	20	5.66	5.95	6.26	6.60	6.95	7.32	7.69		
	15	4.84	5.09	5.38	5.69	6.02	6.38			
10	3.88	4.11	4.37	4.66	4.97					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表 Performance Matrix Table

XR230B-E1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				16.40	20.02	24.26	29.24	35.12	42.11
	60			14.49	17.79	21.63	26.11	31.35	37.51	44.80
	55	10.05	12.61	15.60	19.09	23.15	27.86	33.36	39.79	47.39
	50	10.76	13.47	16.64	20.33	24.60	29.54	35.29	42.01	49.90
	45	11.42	14.28	17.62	21.49	25.97	31.16	37.17	44.17	52.39
	40	12.02	15.03	18.54	22.60	27.30	32.73	39.01	46.33	54.90
	35	12.58	15.73	19.41	23.67	28.59	34.28	40.86	48.51	57.48
	30	13.08	16.38	20.23	24.70	29.86	35.82	42.73	50.76	60.17
	25	13.54	16.99	21.03	25.71	31.13	37.40	44.67	53.12	
	20	13.97	17.58	21.80	26.72	32.42	39.03	46.70		
	15	14.37	18.14	22.57	27.75	33.76	40.75			
10	14.76	18.71	23.36	28.81	35.18					
Input Power	65				16.32	16.99	17.62	18.21	18.75	19.25
	60			14.09	14.75	15.37	15.96	16.52	17.04	17.51
	55	11.54	12.17	12.79	13.40	13.98	14.54	15.07	15.57	16.02
	50	10.53	11.11	11.68	12.24	12.79	13.32	13.82	14.29	14.73
	45	9.65	10.18	10.71	11.23	11.74	12.24	12.72	13.18	13.60
	40	8.88	9.36	9.84	10.33	10.81	11.28	11.74	12.18	12.59
	35	8.17	8.60	9.05	9.50	9.95	10.39	10.83	11.26	11.66
	30	7.48	7.87	8.27	8.69	9.11	9.54	9.96	10.37	10.77
	25	6.77	7.12	7.48	7.87	8.27	8.67	9.08	9.49	
	20	6.00	6.31	6.64	7.00	7.37	7.76	8.16		
	15	5.13	5.40	5.70	6.03	6.39	6.76			
10	4.12	4.36	4.63	4.94	5.27					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表 Performance Matrix Table

XR260B-E1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				18.58	22.68	27.48	33.12	39.79	47.71
	60			16.42	20.15	24.50	29.58	35.51	42.49	50.75
	55	11.38	14.28	17.68	21.63	26.23	31.57	37.79	45.08	53.68
	50	12.19	15.27	18.86	23.03	27.86	33.47	39.98	47.59	56.53
	45	12.94	16.18	19.96	24.35	29.43	35.30	42.11	50.04	59.36
	40	13.62	17.03	21.00	25.61	30.93	37.08	44.20	52.49	62.20
	35	14.25	17.82	21.98	26.81	32.39	38.83	46.29	54.96	65.12
	30	14.82	18.56	22.92	27.98	33.83	40.58	48.41	57.51	68.16
	25	15.34	19.25	23.82	29.12	35.27	42.37	50.60	60.18	
	20	15.83	19.91	24.70	30.27	36.73	44.22	52.91		
	15	16.28	20.56	25.57	31.43	38.25	46.17			
10	16.72	21.19	26.47	32.64	39.85					
Input Power	65				18.81	19.58	20.30	20.98	21.61	22.18
	60			16.24	16.99	17.71	18.40	19.04	19.64	20.19
	55	13.30	14.03	14.74	15.44	16.12	16.76	17.37	17.94	18.47
	50	12.13	12.80	13.46	14.11	14.74	15.35	15.93	16.47	16.98
	45	11.13	11.73	12.34	12.94	13.54	14.11	14.66	15.19	15.68
	40	10.24	10.79	11.35	11.90	12.46	13.00	13.53	14.04	14.51
	35	9.42	9.91	10.42	10.94	11.46	11.98	12.48	12.97	13.44
	30	8.62	9.07	9.53	10.01	10.50	10.99	11.48	11.95	12.42
	25	7.80	8.20	8.63	9.07	9.53	9.99	10.46	10.93	
	20	6.91	7.27	7.65	8.07	8.50	8.94	9.40		
	15	5.91	6.22	6.57	6.95	7.36	7.79			
10	4.75	5.02	5.34	5.69	6.08					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表 Performance Matrix Table

XR280B-E1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				19.80	24.16	29.28	35.29	42.39	50.82
	60			17.49	21.47	26.10	31.51	37.84	45.27	54.07
	55	12.13	15.22	18.83	23.05	27.94	33.63	40.26	48.03	57.19
	50	12.99	16.26	20.09	24.53	29.69	35.66	42.60	50.70	60.23
	45	13.78	17.24	21.27	25.94	31.35	37.61	44.86	53.32	63.24
	40	14.51	18.14	22.38	27.28	32.95	39.50	47.09	55.92	66.27
	35	15.18	18.98	23.42	28.56	34.51	41.37	49.31	58.55	69.37
	30	15.79	19.77	24.42	29.81	36.04	43.24	51.57	61.27	72.62
	25	16.35	20.51	25.38	31.03	37.57	45.14	53.91	64.12	
	20	16.87	21.22	26.31	32.25	39.13	47.11	56.37		
	15	17.35	21.90	27.25	33.49	40.75	49.18			
10	17.81	22.58	28.20	34.78	42.46					
Input Power	65				20.16	20.99	21.77	22.50	23.17	23.78
	60			17.41	18.22	18.99	19.72	20.42	21.06	21.64
	55	14.26	15.04	15.81	16.56	17.28	17.97	18.63	19.24	19.80
	50	13.01	13.72	14.43	15.12	15.80	16.45	17.08	17.66	18.21
	45	11.93	12.58	13.23	13.88	14.51	15.13	15.72	16.28	16.81
	40	10.97	11.57	12.16	12.76	13.36	13.94	14.50	15.05	15.56
	35	10.10	10.63	11.18	11.73	12.29	12.84	13.38	13.91	14.41
	30	9.24	9.72	10.22	10.74	11.26	11.78	12.30	12.82	13.31
	25	8.36	8.79	9.25	9.72	10.21	10.72	11.22	11.72	
	20	7.41	7.79	8.21	8.65	9.11	9.59	10.08		
	15	6.34	6.67	7.05	7.46	7.89	8.35			
10	5.09	5.38	5.72	6.10	6.52					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表 Performance Matrix Table

XR370B-E1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				26.42	32.24	39.07	47.09	56.56	67.82
	60			23.34	28.65	34.83	42.05	50.49	60.41	72.15
	55	16.19	20.30	25.13	30.75	37.29	44.88	53.73	64.09	76.32
	50	17.33	21.70	26.81	32.74	39.61	47.58	56.84	67.65	80.37
	45	18.39	23.00	28.38	34.62	41.83	50.18	59.86	71.14	84.39
	40	19.36	24.21	29.86	36.40	43.97	52.71	62.84	74.62	88.43
	35	20.25	25.33	31.25	38.12	46.05	55.20	65.81	78.14	92.57
	30	21.07	26.38	32.58	39.78	48.09	57.70	68.82	81.76	96.90
	25	21.81	27.37	33.86	41.40	50.13	60.23	71.94	85.56	
	20	22.51	28.31	35.11	43.03	52.22	62.86	75.22		
	15	23.15	29.22	36.36	44.69	54.38	65.63			
10	23.77	30.13	37.62	46.41	56.66					
Input Power	65				26.91	28.01	29.05	30.02	30.92	31.73
	60			23.24	24.31	25.34	26.32	27.24	28.10	28.88
	55	19.03	20.07	21.09	22.09	23.06	23.98	24.85	25.67	26.42
	50	17.36	18.31	19.25	20.18	21.09	21.96	22.79	23.57	24.29
	45	15.92	16.79	17.66	18.52	19.36	20.19	20.98	21.73	22.43
	40	14.64	15.43	16.23	17.03	17.82	18.60	19.36	20.08	20.76
	35	13.47	14.18	14.91	15.65	16.40	17.13	17.86	18.56	19.23
	30	12.33	12.97	13.64	14.32	15.02	15.72	16.42	17.10	17.76
	25	11.16	11.73	12.34	12.97	13.63	14.30	14.97	15.64	
	20	9.89	10.40	10.95	11.54	12.16	12.80	13.45		
	15	8.46	8.90	9.40	9.95	10.53	11.15			
10	6.79	7.18	7.63	8.14	8.70					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表
Performance Matrix Table

XR420B-E1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				30.26	36.94	44.76	53.94	64.79	77.69
	60			26.74	32.82	39.90	48.17	57.83	69.20	82.65
	55	18.54	23.26	28.79	35.23	42.71	51.41	61.54	73.42	87.42
	50	19.86	24.86	30.71	37.50	45.38	54.50	65.11	77.50	92.07
	45	21.07	26.35	32.51	39.66	47.92	57.48	68.57	81.50	96.66
	40	22.18	27.73	34.20	41.70	50.37	60.38	71.98	85.48	101.29
	35	23.20	29.02	35.80	43.66	52.75	63.24	75.38	89.50	106.04
	30	24.13	30.22	37.32	45.56	55.09	66.09	78.84	93.66	111.00
	25	24.99	31.35	38.79	47.43	57.43	69.00	82.41	98.01	
	20	25.78	32.43	40.22	49.29	59.81	72.01	86.16		
	15	26.52	33.48	41.65	51.19	62.29	75.18			
10	27.23	34.51	43.10	53.16	64.90					
Input Power	65				30.82	32.08	33.27	34.39	35.41	36.35
	60			26.62	27.85	29.03	30.15	31.21	32.19	33.08
	55	21.79	22.99	24.16	25.31	26.41	27.47	28.47	29.40	30.26
	50	19.88	20.97	22.06	23.12	24.15	25.15	26.10	27.00	27.83
	45	18.23	19.23	20.22	21.21	22.18	23.12	24.03	24.89	25.69
	40	16.77	17.68	18.59	19.51	20.42	21.31	22.17	23.00	23.79
	35	15.43	16.25	17.08	17.93	18.78	19.63	20.46	21.26	22.03
	30	14.13	14.86	15.62	16.41	17.21	18.01	18.81	19.59	20.35
	25	12.78	13.44	14.13	14.86	15.61	16.38	17.15	17.91	
	20	11.33	11.91	12.54	13.22	13.93	14.66	15.40		
	15	9.69	10.20	10.77	11.40	12.07	12.77			
10	7.78	8.23	8.74	9.33	9.96					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling

性能参数列表 Performance Matrix Table

XR510B-E1-101

kW	Temp Cond. (°C)	Temp. Evap. (°C)								
		-30	-25	-20	-15	-10	-5	0	5	10
Cooling Cap.	65				36.70	44.79	54.28	65.42	78.58	94.22
	60			32.43	39.80	48.39	58.42	70.14	83.92	100.24
	55	22.49	28.21	34.91	42.72	51.80	62.35	74.64	89.04	106.02
	50	24.08	30.15	37.24	45.48	55.03	66.10	78.96	93.99	111.66
	45	25.55	31.95	39.42	48.09	58.12	69.71	83.16	98.84	117.23
	40	26.90	33.63	41.48	50.57	61.08	73.23	87.29	103.66	122.84
	35	28.14	35.19	43.42	52.95	63.97	76.69	91.42	108.55	128.60
	30	29.27	36.65	45.27	55.26	66.81	80.15	95.61	113.58	134.62
	25	30.31	38.02	47.04	57.52	69.65	83.68	99.94	118.86	
	20	31.26	39.33	48.78	59.78	72.54	87.33	104.49		
	15	32.16	40.60	50.51	62.08	75.54	91.18			
10	33.02	41.85	52.27	64.47	78.71					
Input Power	65				37.38	38.91	40.35	41.70	42.95	44.08
	60			32.28	33.77	35.20	36.57	37.85	39.03	40.12
	55	26.43	27.88	29.30	30.69	32.03	33.31	34.53	35.66	36.70
	50	24.11	25.44	26.75	28.04	29.29	30.50	31.66	32.74	33.75
	45	22.11	23.32	24.53	25.72	26.90	28.04	29.14	30.18	31.16
	40	20.34	21.44	22.55	23.66	24.76	25.84	26.89	27.89	28.85
	35	18.71	19.70	20.72	21.75	22.78	23.80	24.81	25.78	26.72
	30	17.13	18.02	18.95	19.90	20.87	21.84	22.81	23.76	24.68
	25	15.50	16.30	17.14	18.02	18.94	19.86	20.80	21.73	
	20	13.74	14.44	15.21	16.03	16.89	17.78	18.68		
	15	11.75	12.37	13.06	13.82	14.63	15.49			
10	9.43	9.98	10.60	11.31	12.08					

Capacity Calculation Based On SH=11.1K And Zero Sub Cooling